



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

#### SEAJET 012 UNIVERSAL PRIMER-UNDERCOAT

Product code: 211ADT - Version 1 - Date:25-07-2023

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Paint and/or related product.

### 1.3. Details of the supplier of the safety data sheet

Chugoku Paints B.V., Sluisweg 12, 4794 SW Heijningen, Po Box 73, 4793 ZH Fijnaart, The Netherlands, Tel.+31-167-526100, E-mail: msdsregistration@cmpeurope.eu

### 1.4. Emergency telephone number

National Poisons Information Centre (NPIC) Tel. 01 809 2566 - 24/7

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 H226	Flammable liquid and vapour.
STOT SE 3 H336	May cause drowsiness or dizziness.
Aquatic Chronic 2 H411	Toxic to aquatic life with long lasting effects.

### 2.2. Label elements



GHS02



GHS07



GHS09

**Hazard pictogram(s):**

**Signal word: Warning**

#### Labelling according to Regulation (EC) No 1272/2008 [CLP]:

##### Hazard statement(s):

H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

#### Supplemental hazard information (EU):

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.



Product code: 211ADT - Version 1 - Date:25-07-2023

**Precautionary statement(s)**

## Prevention:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261: Avoid breathing vapours/spray.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

## Response:

P391: Collect spillage.

## Storage &amp; Disposal:

P501: Dispose of contents, container to a hazardous or special waste collection point.

**Contains (EC 1272/2008 18.3(b)):**

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic, &lt;2% aromatics.

Extended details regarding health and environment, see Section 11 &amp; 12.

**2.3. Other hazards**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.



Product code: 211ADT - Version 1 - Date:25-07-2023

**SECTION 3: Composition/information on ingredients**
**3.2. Mixtures**


Substances presenting a health or environmental hazard within the meaning of Regulation (EC) No. 1272/2008, assigned a Community workplace exposure limit, classified as PBT/vPvB or included in the Candidate List. (\*) For full text of H-statements, see SECTION 16.

Substance name	Identification number	% [weight]	Hazard statement Code(s) (*) / Hazard Class and Category Codes
Hydrocarbons, C9-C11, N-Alkanes, Iso-Alkanes, Cyclic, <2% Aromatics.	EG-nr: 919-857-5	20-25 %	H226 - Flam. Liq. 3
	CAS-nr: 64742-48-9		H304 - Asp. Tox. 1
	Index: -		H336 - STOT SE 3
	Reach#: 01-2119463258-33		EUH066
Zinc Oxide.	EG-nr: 215-222-5	1-4 %	H400 - Aquatic Acute 1
	CAS-nr: 1314-13-2		H410 - Aquatic Chronic 1
	Index: 030-013-00-7		
	Reach#: 01-2119463881-32		
Reaction Mass Of Ethylbenzene And Xylene.	EG-nr: 905-588-0	1-3 %	H226 - Flam. Liq. 3
	CAS-nr: -		H304 - Asp. Tox. 1
	Index: -		H312 - Acute Tox. 4
	Reach#: 01-2119488216-32		H315 - Skin Irrit. 2
Methanol.	EG-nr: 200-659-6	0,1-0,2 %	H225 - Flam. Liq. 2
	CAS-nr: 67-56-1		H331 - Acute Tox. 3
	Index: 603-001-00-X		H311 - Acute Tox. 3
	Reach#: 01-2119433307-44		H301 - Acute Tox. 3


!Contains Titaniumdioxide. ≥1%. (CAS 13463-67-7) The Annex VI classification of Titanium dioxide does not apply to this mixture according to its Note 10. (EU) 2020/217




Product code: 211ADT - Version 1 - Date:25-07-2023

**SECTION 4: First aid measures****4.1. Description of first aid measures**


Pay attention to your own safety! In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

**following inhalation:**


Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

**following skin contact:**

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

**following eye contact:**

Remove contact lenses, if present and easy to do. Irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

**following ingestion:**

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed****Potential acute symptoms and effects****following inhalation:**

Exposure to vapours may cause a health hazard. Serious effects may be delayed following exposure.

May cause drowsiness or dizziness.

**following skin contact:**

No known significant effects or critical hazards.

**following eye contact:**

No known significant effects or critical hazards.

**following ingestion:**

No known significant effects or critical hazards.

**Potential delayed symptoms and effects****following inhalation:**

No specific data.

**following skin contact:**

Adverse symptoms may include the following: irritation, redness

**following eye contact:**

Adverse symptoms may include the following: irritation, watering, redness

**following ingestion:**

No specific data.

**4.3. Indication of any immediate medical attention and special treatment needed****Notes to physician**

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**

No specific treatment.



Product code: 211ADT - Version 1 - Date:25-07-2023

**SECTION 5: Firefighting measures****5.1. Extinguishing media**

Recommended: alcohol resistant foam, CO2, powders.

**Extinguishing media which must not be used for safety reasons:**

Water jet. Zinc dust containing products should not be extinguished with water.

**5.2. Special hazards arising from the substance or mixture**

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. See Section 10.

**5.3. Advice for firefighters**

There is no one clothing material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Fire fighter's clothing conforming to European standard EN469 provides a basic level of protection for chemical incidents. Appropriate breathing apparatus may be required (Self-Contained Breathing Apparatus (SCBA)). Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel: Comply with company's emergency procedures. Exclude sources of ignition and ventilate the area. Use safety goggles or safety glasses, as well as any other appropriate personal protective equipment, at all times. Avoid breathing vapours. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Refer to protective measures listed in Sections 7 and 8.

For emergency responders: See Section 8 for information on appropriate personal protective equipment. See also the information: "For non-emergency personnel".

**6.2. Environmental precautions**

Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

**6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Place in a suitable container. Clean preferably with a detergent - avoid use of solvents.

**6.4. Reference to other sections**

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. No sparking tools should be used. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Smoking, eating and drinking should be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses. Isolate from sources of heat, sparks and open flame. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting self-closing lids or laid out flat in a single layer to dry. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

**Information regarding fire and explosion hazard**

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in accordance with local regulations.



Product code: 211ADT - Version 1 - Date:25-07-2023

**Notes on joint storage**

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

**Additional information on storage conditions**

Observe label precautions. Store between 0°C and 40°C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

**7.3. Specific end use(s)**

Application: Airless spray, Brush, Roller (See also Technical Data Sheet.)

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

Limits for occupational exposure and / or biological limit values		
	LIMIT VALUES TWA8h - STEL15 ppm-mg/m <sup>3</sup>	LIMIT VALUES TWA8h - STEL15 ppm-mg/m <sup>3</sup>
Hydrocarbons, C9-C11, N-Alkanes, Iso-Alkanes, Cyclic, <2% Aromatics.	TWA8h - ppm / - mg/m <sup>3</sup>	TWA8h - ppm / - mg/m <sup>3</sup>
	STEL - ppm / - mg/m <sup>3</sup>	STEL15 - ppm / - mg/m <sup>3</sup>
	Notes -	Notation -
Zinc Oxide.	TWA8h - ppm / - mg/m <sup>3</sup>	TWA8h - ppm / - mg/m <sup>3</sup>
	STEL - ppm / - mg/m <sup>3</sup>	STEL15 - ppm / - mg/m <sup>3</sup>
	Notes -	Notation -
Reaction Mass Of Ethylbenzene And Xylene.	TWA8h - ppm / - mg/m <sup>3</sup>	TWA8h - ppm / - mg/m <sup>3</sup>
	STEL - ppm / - mg/m <sup>3</sup>	STEL15 - ppm / - mg/m <sup>3</sup>
	Notes -	Notation -
Methanol.	TWA8h 200 ppm / 260 mg/m <sup>3</sup>	TWA8h 200 ppm / 260 mg/m <sup>3</sup>
	STEL - ppm / - mg/m <sup>3</sup>	STEL15 - ppm / - mg/m <sup>3</sup>
	Notes Sk, IOELV	Notation Skin

Ireland - TWA=Time Weighted Average (8hr) - STEL=Short-term exposure limit (15-minute reference period) - Health and Safety Authority - Code of Practice.

Europe - TWA = Time Weight Average (8hr) - Measured or calculated in relation to a reference period of 8 hours time-weighted average (TWA) - STEL = Short-term exposure limit - A limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified - SCOEL

Notes / Notations:

BOELV: Binding Occupational Exposure Limit Values

Carc.1A: substances known to have carcinogenic potential for humans; classification is largely based on human evidence to which the EU Classification, Labelling and Packaging Regulation (EC) No.1272/2008 applies and as defined in the Safety, Health and Welfare at Work (Carcinogens) (Amendment) Regulations 2015.

Carc.1B: substances presumed to have carcinogenic potential for humans; classification is largely based on animal evidence to which Classification, Labelling and Packaging Regulation (EC) No. 1272/2008 apply and as defined in the Safety, Health and Welfare at Work (Carcinogens)(Amendment) Regulations 2015.

Inh.: Inhalable fraction.

IOELV: Indicative Occupational Exposure Limit Values.

Muta.1A: substances which are known to induce heritable mutations in the germ cells of humans; classification is based on positive evidence from human studies to which the Regulation (EC) No. 1272/2008 on Classification, Labelling and



Product code: 211ADT - Version 1 - Date:25-07-2023

Packaging of substances and mixtures apply and as defined in the Safety, Health and Welfare at Work (Carcinogens) (Amendment) Regulations 2015.

Muta.1B: substances which should be regarded as if they induce heritable mutations in the germ cells of humans; classification is based on evidence from mutagenicity tests in mammals or humans, to which the Regulation (EC) No. 1272/2008 on Classification, Labelling and Packaging of substances and mixtures apply and as defined in the Safety, Health and Welfare at Work (Carcinogens) (Amendment) Regulations 2015.

Inhalable Fraction and Vapour (IFV): the Inhalable Fraction and Vapour note is used when a material exerts sufficient vapour pressure such that it may be present in both particle and vapour phases.

Repr.1A: substances which are known human reproductive toxicants, largely based on evidence from human studies to which the Regulation (EC) No.1272/2008 on Classification, Labelling and Packaging of substances and mixtures apply.

Repr.1B: substances which are presumed human reproductive toxicants, largely based on data from animal studies, to which the Regulation (EC) No. 1272/2008 on Classification, Labelling and Packaging of substances and mixtures apply.

Resp.: Respirable fraction.

Respirable Fraction (R): particles of inhalable aerosols that are inhaled and are not captured in the upper airways (nasopharyngeal and tracheobronchial regions) but penetrate to the pulmonary region containing the respiratory bronchioles, alveolar ducts and alveolar sacs are considered to comprise of the Respirable Fraction of the aerosol.

Sens.: in the workplace respiratory or dermal exposures to sensitising agents may occur.

Sk: substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body.

Skin: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin.

DNEL - Not available.

PNEC - Not available.

## 8.2. Exposure controls


### Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

### Individual protection measures, such as personal protective equipment


#### Personal Protection

##### Respiratory protection

 If workers could be exposed to concentrations above the exposure limit they should use a respirator to EN 140, fitted with a filter suitable for both particulates and vapours to EN14387, with an assigned protection factor of at least 10 (e.g. A2P3).

Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

##### Hand protection

 There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. At repeated or prolonged contact; use gloves tested according to EN 374. Viton-gloves offer good protection for intense contact with most solvents, e.g. complete immersion in solvent.

Nitrile gloves offer good protection during spray application. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. The breakthrough time must be greater than the end use time of the product. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

<b>Gloves for repeated or prolonged exposure (Permeation breakthrough times &gt; 480 min) - High Protection:</b>		
<b>Material:</b>	<b>Minimum Thickness:</b>	<b>Chemical resistance:</b>
Polyethylene (PE) Gloves	0,062mm	High
Butyl Viton Gloves	0,70mm	High





Product code: 211ADT - Version 1 - Date:25-07-2023

<b>Gloves for repeated or prolonged exposure (Permeation breakthrough times 240 - 480 min) - High Protection:</b>		
<b>Material:</b>	<b>Minimum Thickness:</b>	<b>Chemical resistance:</b>
Polyethylene (PE) Gloves	0,062mm	High
Butyl Viton Gloves	0,70mm	High
<b>Gloves for repeated or prolonged exposure (Permeation breakthrough times 120-240 min) - Medium Protection:</b>		
<b>Material:</b>	<b>Minimum Thickness:</b>	<b>Chemical resistance:</b>
Polyethylene (PE) Gloves	0,062mm	High
Butyl Viton Gloves	0,70mm	High
<b>Gloves for repeated or prolonged exposure (Permeation breakthrough times 60 - 120 min) - Medium Protection:</b>		
<b>Material:</b>	<b>Minimum Thickness:</b>	<b>Chemical resistance:</b>
Polyethylene (PE) Gloves	0,062mm	High
Butyl Viton Gloves	0,70mm	High
<b>Gloves for short term exposure / splash protection (Permeation breakthrough times 30 - 60 min):</b>		
<b>Material:</b>	<b>Minimum Thickness:</b>	<b>Chemical resistance:</b>
Polyethylene (PE) Gloves	0,062mm	High
Butyl Viton Gloves	0,70mm	High
Nitrile Gloves	0,31mm	High
<b>Gloves for short term exposure / splash protection (Permeation breakthrough times 10 - 30 min):</b>		
<b>Material:</b>	<b>Minimum Thickness:</b>	<b>Chemical resistance:</b>
Polyethylene (PE) Gloves	0,062mm	High
Butyl Viton Gloves	0,70mm	High
Neoprene Gloves	<0,4mm	High
Nitrile Gloves	0,175mm	High
<b>Non suitable Gloves - non exhaustive list (Permeation breakthrough times &lt; 10 min):</b>		
<b>Material:</b>	<b>Thickness (or less):</b>	
Natural Rubber Gloves	0,75mm	
Nitrile Gloves	-	
Neoprene Gloves	0,75mm	
Butyl Gloves	0,50mm	
PVA Gloves	0,2-0,3mm	

Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing. USE PE gloves as under gloves for difficult situations like for instance: high exposure, unknown composition or unknown properties of the chemicals.


**Eye/face protection**

Use safety eyewear tested according to EN 166 designed to protect against splash of liquids.


**Skin protection**

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.


**Environmental exposure controls**

Do not allow to enter drains or water courses.





Product code: 211ADT - Version 1 - Date:25-07-2023

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**(a) Physical state**

Liquid

**(b) Colour**

White.

**(c) Odour**

Petroleum-like odour.

**(d) Melting point/freezing point**

Not applicable due to nature of the product.

**(e) Boiling point or initial boiling point and boiling range**

Not applicable due to nature of the product. Lowest Boiling Point: Methanol. - 64°C

**(f) Flammability**

Vapours are ignitable. See Flash point (h).

**(g) Lower and upper explosion limit**

The product itself is not explosive, but the formation of an explosive mixture of vapour or dust with air is possible.

Hydrocarbons, C9-C11, N-Alkanes, Iso-Alkanes, Cyclic, <2% Aromatics.	0.6-7.0%
Zinc Oxide.	Not applicable.
Reaction Mass Of Ethylbenzene And Xylene.	1.0-7.0%
Methanol.	5.5-44%

**(h) Flash point**

37°C - Method: ISO13736:2021

**(i) Auto-ignition temperature**

Not applicable due to nature of the product. Lowest Boiling Point: Methanol. - 64°C

**(j) Decomposition temperature**

Not applicable due to nature of the product.

**(k) pH**

Not applicable due to nature of the product. Mixture is non-soluble (in water).

**(l) Kinematic viscosity**

349 mm<sup>2</sup>/s @40°C - Method: ISO3219

Non-Newtonian liquid - thixotropic behaviour.

**(m) Solubility**

Not Soluble (in water).

**(n) Partition coefficient n-octanol/water (log value)**

Not applicable due to nature of the product.

**(o) Vapour pressure**

Hydrocarbons, C9-C11, N-Alkanes, Iso-Alkanes, Cyclic, <2% Aromatics.	0,2 kPa
Zinc Oxide.	Not applicable.
Reaction Mass Of Ethylbenzene And Xylene.	8.21 mbar
Methanol.	128 mbar



Product code: 211ADT - Version 1 - Date:25-07-2023

**(p) Density and/or relative density**

Relative density 1,37 @ 20°C - Method: ASTM D1475-98

**(q) Relative vapour density**

1-2 @ 20°C - Method: Calculated.

**(r) Particle characteristics**

Not applicable due to nature of the product.

**9.2. Other information**

Information with regard to physical hazard classes

No relevant information.

Other safety characteristics

No relevant information.

**SECTION 10: Stability and reactivity**

---

**10.1. Reactivity**

No specific test data related to reactivity available for this product or its ingredients.

**10.2. Chemical stability**

Stable under recommended storage and handling conditions (see Section 7).

**10.3. Possibility of hazardous reactions**

In combination with oxidizing agents, strongly alkaline and strongly acid materials, exothermic reactions and/or explosive reactions may occur or toxic vapours may arise. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting self-closing lids or laid out flat in a single layer to dry. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

**10.4. Conditions to avoid**

When exposed to high temperatures may produce hazardous decomposition products.

**10.5. Incompatible materials**

Keep away from oxidising agents, strongly alkaline and strongly acid materials.

**10.6. Hazardous decomposition products**

Carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

**SECTION 11: Toxicological information**

---

There are no data available on the mixture itself. The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.



Product code: 211ADT - Version 1 - Date:25-07-2023

**Substance name**

Hydrocarbons, C9-C11, N-Alkanes, Iso-Alkanes, Cyclic, &lt;2% Aromatics. - LD50 Oral - &gt;5000 mg/kg, Rat - LD50 Dermal - &gt;2000 mg/kg, Rat - LC50 Inhalation - &gt;4951 mg/lRat,4h

Zinc Oxide. - LD50 Oral - &gt;5000 mg/kg, Rat - LD50 Dermal - Not available. - LC50 Inhalation - &gt;5700 mg/m3Rat,4h

Reaction Mass Of Ethylbenzene And Xylene. - LD50 Oral - &gt;2000 mg/kg, Rat - LD50 Dermal - &gt;2000 mg/kg, Rat - LC50 Inhalation - 29 mg/lRat,4h

Methanol. - LD50 Oral - 5628 mg/kg, Rat - LD50 Dermal - 15800 mg/kg, Rabbit - LC50 Inhalation - 2,8 mg/kgRat,4h

**Conclusion/Summary on mixture****Acute toxicity:**

ATEmix (oral) : No specific data.

ATEmix (Dermal) : No specific data.

ATEmix (Inhalation) : No specific data.

**Skin corrosion/irritation:**

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met.

Justification: Additivity approach, No testdata available.

**Serious eye damage/irritation:**

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met.

Justification: Additivity approach, No testdata available.

**Respiratory or skin sensitisation:**

Conclusion/Summary on mixture

Respiratory sensitization Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

Skin sensitization Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

**Germ cell mutagenicity:**

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

**Carcinogenicity:**

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

**Reproductive toxicity:**

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

**STOT - single exposure:**

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

**STOT - repeated exposure:**

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

**Aspiration hazard:**

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met.

Justification: Additivity approach / Kinematic viscosity: 349 mm<sup>2</sup>/s @40°C - Measured**Information on likely routes of exposure**

Inhalation: No known significant effects or critical hazards.

Ingestion: No specific data.



Product code: 211ADT - Version 1 - Date:25-07-2023

Skin exposure: No specific data.

Eye exposure: No specific data.

**Symptoms related to the physical, chemical and toxicological characteristics**

Inhalation: No specific data.

Ingestion: No specific data.

Skin exposure: Adverse symptoms may include the following: irritation, redness.

Eye exposure: Adverse symptoms may include the following: irritation, watering, redness.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

Short term exposure:

Potential immediate effects: No specific data.

Potential delayed effects: No specific data.

Long term exposure:

Potential immediate effects: No specific data.

Potential delayed effects: No specific data.

**Potential chronic health effects:**

**Conclusion/Summary on mixture**

General: No known significant effects or critical hazards.

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: No known significant effects or critical hazards.

Developmental effects: No known significant effects or critical hazards.

Fertility effects: No known significant effects or critical hazards.

Other information: No relevant information.

**11.2 Information on other hazards**

**Endocrine disrupting properties**

No relevant information.

**Other information**

No relevant information.

**SECTION 12: Ecological information**

There are no data available on the mixture itself. Do not allow to enter drains or water courses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and classified for eco-toxicological hazards accordingly.

**12.1. Toxicity**

**Substance name - Species - Exposure - Results**

Hydrocarbons, C9-C11, N-Alkanes, Iso-Alkanes, Cyclic, <2% Aromatics. Acute (short-term) toxicity: Fish: LC50/96h >1000 mg/l (Oncorhynchus mykiss), Crustacea: EC50/48h >1000 mg/l (Daphnia magna), Algae/aquatic plants: EC50/72h >1000 mg/L (Pseudokirchneriella subcapitata), Other organisms: Not available. Chronic (long-term) toxicity: Fish: NOELR 0.131 mg/L, Crustacea: NOELR 0.23 mg/L, Algae/aquatic plants: NOEL >100 mg/L, Other organisms: Not available.

Zinc Oxide. Acute (short-term) toxicity: Fish: LC50 0,169 mg Zn/l (Oncorhynchus Mykiss), Crustacea: EC50/48h - 0.413 mg/l (Ceriodaphnia dubia), Algae/aquatic plants: EC50/72h - 0,137 mg/l (Selenastrum Capricornutum), Other organisms: Not available. Chronic (long-term) toxicity: Fish: NOEC 0.025 mg Zn/l, Crustacea: NOEC 82 ug/l, Algae/aquatic plants: NOEC 19 ug/l (Pseudokirchneriella subcapitata), Other organisms: Not available.



Product code: 211ADT - Version 1 - Date:25-07-2023

**Substance name - Species - Exposure - Results**

Reaction Mass Of Ethylbenzene And Xylene. Acute (short-term) toxicity: Fish: LC50/96h - 2.6 mg/l, Crustacea: EC50/48h 1-10 mg/l (Daphnia magna), Algae/aquatic plants: EC50/72h 2.2 mg/L (Pseudokirchneriella subcapitata), Other organisms: Not available. Chronic (long-term) toxicity: Fish: NOEC >1.3 mg/L (Salmo gairdneri), Crustacea: NOEC 0.96mg/L, Algae/aquatic plants: NOEC 0.44mg/L, Other organisms: Not available.

Methanol. Acute (short-term) toxicity: Fish: LC50/96h 15400 mg/l (Lepomis macrochirus), Crustacea: EC50/48h >10000mg/L (Daphnia magna), Algae/aquatic plants: EC50/96h 22000 mg/L (Selenastrum capricornutum ), Other organisms: Not available. Chronic (long-term) toxicity: Fish: NOEC 450 mg/L, Crustacea: NOEC 208 mg/L, Algae/aquatic plants: Not available., Other organisms: Not available.

**12.2. Persistence and degradability**

**Substance name**

Hydrocarbons, C9-C11, N-Alkanes, Iso-Alkanes, Cyclic, <2% Aromatics. - Readily biodegradable.

Zinc Oxide. - Readily biodegradable.

Reaction Mass Of Ethylbenzene And Xylene. - Readily biodegradable.

Methanol. - Readily biodegradable.

**12.3. Bioaccumulative potential**

**Substance name**

Hydrocarbons, C9-C11, N-Alkanes, Iso-Alkanes, Cyclic, <2% Aromatics.

**log Kow**

Not available.

**BCF**

Not available.

Zinc Oxide.

Not available.

Not available.

Reaction Mass Of Ethylbenzene And Xylene.

3,1

25,9

Methanol.

-0,74

<10

**12.4. Mobility in soil**

Soil/water partition coefficient (KOC)

: Not available.

Mobility

: No relevant information.



Product code: 211ADT - Version 1 - Date:25-07-2023

**12.5. Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6. Endocrine disrupting properties**

No relevant information.

**12.7. Other adverse effects**

No relevant information.






**SECTION 13: Disposal considerations**
**13.1. Waste treatment methods**

Product / Packaging disposal: Dispose of containers contaminated by the product in accordance with local or national legal provisions. The European Waste Catalogue (2014/955/EC) classification of this product. Waste codes / waste designations according to LoW: 08 01 11\* Waste paint and varnish containing organic solvents or other hazardous substances. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information contact your local waste authority. Waste should not be disposed of by release to sewers. Using information provided in this safety data sheet, advice should be obtained from the local waste authority on the classification of empty containers.

Containers which are not properly cleaned may contain (highly) flammable or explosive vapours.

Special precautions: Use appropriate protective equipment for the removal and / or disposal of this product.

**SECTION 14: Transport information**

	ADR / RID / ADN	IMDG-Code	IATA
14.1. UN number or ID number	UN 1263	UN 1263	UN 1263
14.2. UN proper shipping name	PAINT	PAINT	PAINT
14.3. Transport hazard class(es)	3	3	3
Label(s)			
14.4. Packing group	III	III	III
14.5. Environmental hazards	Yes Environmental hazardous substances (aquatic environment) 	Yes Marine Pollutant: Yes  Marine Pollutant substance(s): Zinc Oxide.	No
Additional information	Hazard Identification Number No.: 30	Emergency Schedule Number (EmS): F-E, S-E	



Product code: 211ADT - Version 1 - Date:25-07-2023

**14.6. Special precautions for user**

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7. Maritime transport in bulk according to IMO instruments**

Not applicable.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

The information in this Safety Data Sheet is required pursuant to Annex II to regulation (EC) No 1907/2006 and its amendments.

The provisions of the Health and Safety at Work etc. Act [and the Control of Substances Hazardous to Health Regulations] apply to the use of this product at work.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

Seveso category (DIRECTIVE 2012/18/EU): P5c - E2 This product may add to the calculation for determining whether a site is within scope of the Seveso Directive on major accident hazards.

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

**SECTION 16: Other information****Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008****[CLP]:**

H226	Measured
H336	Additivity approach
H411	Summation method

**Abbreviations and acronyms:**

ADN	: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	: Acute Toxicity Estimate
BCF	: Bioconcentration factor
CLP	: Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DNEL	: Derived No Effect Level
IATA	: International Air Transport Association
IMDG-Code	: International Maritime Dangerous Goods Code
Kow	: octanol-water partition coefficient
LC50	: Lethal Concentration to 50 % of a test population
LD50	: Lethal Dose to 50% of a test population (Median Lethal Dose)
PBT	: Persistent, Bioaccumulative and Toxic substance





Product code: 211ADT - Version 1 - Date:25-07-2023

- PNEC : Predicted No Effect Concentration(s)  
RID : Regulations concerning the International Carriage of Dangerous Goods by Rail  
STOT : Specific Target Organ Toxicity  
vPvB : Very Persistent and Very Bioaccumulative

**Full text of Hazard Statements appearing in Section 3.2.:**

- EUH066 Repeated exposure may cause skin dryness or cracking.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H301 Toxic if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H311 Toxic in contact with skin.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H370\*\* Causes damage to organs.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.

The information of this SDS is based on the present state of our knowledge and on current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

**SEAJET 012 UNIVERSAL PRIMER-UNDERCOAT**

**Safe Use of Mixtures Information for end-users (SUMI)**

**Title: Professional spray painting, near-industrial setting - CEPE\_PW\_01**

**This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.**

**General description of the process covered**




Indoor spray painting by professionals with efficient ventilation such as spray booth or local exhaust ventilation.

This safe use information is linked to: SWED CEPE\_PW\_01

**Operational Conditions**

Indoor use.

Maximum duration of individual exposure: covers daily use up to 8 hours, 225 days per year \*

<b>Risk Management Measures</b>			
<b>Contributing activity</b>	<b>Ventilation</b>		<b>Ventilation - air changes/hr</b>
Preparation of material for application	Enhanced (mechanical) room ventilation		5-10
Loading of application equipment and handling of coated parts before curing	Enhanced (mechanical) room ventilation		5-10
Application	Local exhaust ventilation, spray booth or equivalent		Refer to relevant technical standards
Application equipment cleaning	Enhanced (mechanical) room ventilation		5-10
Waste management	Enhanced (mechanical) room ventilation		5-10
<b>Contributing activity</b>	<b>Respiratory</b> 	<b>Eye</b> 	<b>Hands</b> 
Preparation of material for application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Loading of application equipment and handling of coated parts before curing	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application equipment cleaning	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Waste management	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374

See Section 8 of this Safety Data Sheet for specifications.

In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

Disclaimer: The information in this Safe Use of Mixtures Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product. No liability is accepted for any damage, no matter of what kind, which is the direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

**SEAJET 012 UNIVERSAL PRIMER-UNDERCOAT**

**Safe Use of Mixtures Information for end-users (SUMI)**

**Title: Professional non-spray painting, near-industrial setting - CEPE\_PW\_02**

**This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.**

**General description of the process covered**




Indoor painting by professionals with brush, roller, putty knife etc. with enhanced ventilation or local exhaust ventilation

This safe use information is linked to: SWED CEPE\_PW\_02

**Operational Conditions**

Indoor use.

Maximum duration of individual exposure: covers daily use up to 8 hours, 225 days per year \*

<b>Risk Management Measures</b>			
<b>Contributing activity</b>	<b>Ventilation</b>		<b>Ventilation - air changes/hr</b>
Preparation of material for application	Enhanced (mechanical) room ventilation		5-10
Loading of application equipment and handling of coated parts before curing	Enhanced (mechanical) room ventilation		5-10
Application	Local exhaust ventilation		Refer to relevant technical standards
Application equipment cleaning	Enhanced (mechanical) room ventilation		5-10
Waste management	Enhanced (mechanical) room ventilation		5-10
<b>Contributing activity</b>	<b>Respiratory</b> 	<b>Eye</b> 	<b>Hands</b> 
Preparation of material for application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Loading of application equipment and handling of coated parts before curing	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application equipment cleaning	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Waste management	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374

See Section 8 of this Safety Data Sheet for specifications.

In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

Disclaimer: The information in this Safe Use of Mixtures Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product. No liability is accepted for any damage, no matter of what kind, which is the direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

**SEAJET 012 UNIVERSAL PRIMER-UNDERCOAT**

**Safe Use of Mixtures Information for end-users (SUMI)**

**Title: Professional spray painting, indoor (without respiratory protection) - CEPE\_PW\_03a**

**This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.**

**General description of the process covered**



Indoor spray painting by professionals for general applications (e.g. decorative), with general room ventilation only (open doors/windows).

This safe use information is linked to: SWED CEPE\_PW\_03a

**Operational Conditions**

Indoor use.

Maximum duration of individual exposure: covers daily use up to 8 hours, 225 days per year \*

<b>Risk Management Measures</b>			
<b>Contributing activity</b>	<b>Ventilation</b>	<b>Ventilation - air changes/hr</b>	
Preparation of material for application	Good general room ventilation (e.g. open windows)	3-5	
Loading of application equipment and handling of coated parts before curing	Good general room ventilation (e.g. open windows)	3-5	
Application	Good general room ventilation (e.g. open windows)	3-5	
Application equipment cleaning	Good general room ventilation (e.g. open windows)	3-5	
Waste management	Good general room ventilation (e.g. open windows)	3-5	
<b>Contributing activity</b>	<b>Respiratory</b>	<b>Eye</b> 	<b>Hands</b> 
Preparation of material for application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Loading of application equipment and handling of coated parts before curing	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application equipment cleaning	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Waste management	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374

See Section 8 of this Safety Data Sheet for specifications.

In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

Disclaimer: The information in this Safe Use of Mixtures Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product. No liability is accepted for any damage, no matter of what kind, which is the direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

**SEAJET 012 UNIVERSAL PRIMER-UNDERCOAT**

**Safe Use of Mixtures Information for end-users (SUMI)**

**Title: Professional spray painting, indoor (with respiratory protection) - CEPE\_PW\_03b**

**This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.**

**General description of the process covered**




Indoor spray painting by professionals for specialist applications, with general room ventilation plus respiratory protection.

This safe use information is linked to: SWED CEPE\_PW\_03b

**Operational Conditions**

Indoor use.

Maximum duration of individual exposure: covers daily use up to 8 hours, 225 days per year \*

<b>Risk Management Measures</b>			
<b>Contributing activity</b>	<b>Ventilation</b>		<b>Ventilation - air changes/hr</b>
Preparation of material for application	Good general room ventilation (e.g. open windows)		3-5
Loading of application equipment and handling of coated parts before curing	Good general room ventilation (e.g. open windows)		3-5
Application	Good general room ventilation (e.g. open windows)		3-5
Application equipment cleaning	Good general room ventilation (e.g. open windows)		3-5
Waste management	Good general room ventilation (e.g. open windows)		3-5
<b>Contributing activity</b>	<b>Respiratory</b> 	<b>Eye</b> 	<b>Hands</b> 
Preparation of material for application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Loading of application equipment and handling of coated parts before curing	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application equipment cleaning	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Waste management	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374

See Section 8 of this Safety Data Sheet for specifications.

In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

Disclaimer: The information in this Safe Use of Mixtures Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product. No liability is accepted for any damage, no matter of what kind, which is the direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

**SEAJET 012 UNIVERSAL PRIMER-UNDERCOAT**

**Safe Use of Mixtures Information for end-users (SUMI)**

**Title: Professional painting, indoor brush/roller - CEPE\_PW\_04**

**This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.**

**General description of the process covered**



Indoor painting by professionals with brush or roller, with general room ventilation (open doors/windows).

This safe use information is linked to: SWED CEPE\_PW\_04

**Operational Conditions**

Indoor use.

Maximum duration of individual exposure: covers daily use up to 8 hours, 225 days per year \*

<b>Risk Management Measures</b>			
<b>Contributing activity</b>	<b>Ventilation</b>	<b>Ventilation - air changes/hr</b>	
Preparation of material for application	Good general room ventilation (e.g. open windows)	3-5	
Loading of application equipment and handling of coated parts before curing	Good general room ventilation (e.g. open windows)	3-5	
Application	Good general room ventilation (e.g. open windows)	3-5	
Application equipment cleaning	Good general room ventilation (e.g. open windows)	3-5	
Waste management	Good general room ventilation (e.g. open windows)	3-5	
<b>Contributing activity</b>	<b>Respiratory</b>	<b>Eye</b> 	<b>Hands</b> 
Preparation of material for application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Loading of application equipment and handling of coated parts before curing	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application equipment cleaning	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Waste management	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374

See Section 8 of this Safety Data Sheet for specifications.

In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

Disclaimer: The information in this Safe Use of Mixtures Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product. No liability is accepted for any damage, no matter of what kind, which is the direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

**SEAJET 012 UNIVERSAL PRIMER-UNDERCOAT**

**Safe Use of Mixtures Information for end-users (SUMI)**

**Title: Professional spray painting, outdoor (without respiratory protection) - CEPE\_PW\_05a**

**This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.**

**General description of the process covered**



Outdoor spray painting by professionals for general applications (e.g. decorative).

This safe use information is linked to: SWED CEPE\_PW\_05a

**Operational Conditions**

Outdoor use.

Maximum duration of individual exposure: covers daily use up to 8 hours, 225 days per year \*

<b>Risk Management Measures</b>			
<b>Contributing activity</b>	<b>Ventilation</b>	<b>Ventilation - air changes/hr</b>	
Preparation of material for application	Outdoors	3-5	
Loading of application equipment and handling of coated parts before curing	Outdoors	3-5	
Application	Outdoors	3-5	
Application equipment cleaning	Outdoors	3-5	
Waste management	Outdoors	3-5	
<b>Contributing activity</b>	<b>Respiratory</b>	<b>Eye</b> 	<b>Hands</b> 
Preparation of material for application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Loading of application equipment and handling of coated parts before curing	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application equipment cleaning	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Waste management	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374

See Section 8 of this Safety Data Sheet for specifications.

In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

Disclaimer: The information in this Safe Use of Mixtures Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product. No liability is accepted for any damage, no matter of what kind, which is the direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.



**SEAJET 012 UNIVERSAL PRIMER-UNDERCOAT**

**Safe Use of Mixtures Information for end-users (SUMI)**

**Title: Professional spray painting, outdoor (with respiratory protection) - CEPE\_PW\_05b**

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

**General description of the process covered**




Outdoor spray painting by professionals for specialist applications, with respiratory protection.

This safe use information is linked to: SWED CEPE\_PW\_05b

**Operational Conditions**

Outdoor use.

Maximum duration of individual exposure: covers daily use up to 8 hours, 225 days per year \*

<b>Risk Management Measures</b>			
<b>Contributing activity</b>	<b>Ventilation</b>	<b>Ventilation - air changes/hr</b>	
Preparation of material for application	Outdoors	3-5	
Loading of application equipment and handling of coated parts before curing	Outdoors	3-5	
Application	Outdoors	3-5	
Application equipment cleaning	Outdoors	3-5	
Waste management	Outdoors	3-5	
<b>Contributing activity</b>	<b>Respiratory</b> 	<b>Eye</b> 	<b>Hands</b> 
Preparation of material for application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Loading of application equipment and handling of coated parts before curing	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application equipment cleaning	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Waste management	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374

See Section 8 of this Safety Data Sheet for specifications.

In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

Disclaimer: The information in this Safe Use of Mixtures Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product. No liability is accepted for any damage, no matter of what kind, which is the direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

**SEAJET 012 UNIVERSAL PRIMER-UNDERCOAT**

**Safe Use of Mixtures Information for end-users (SUMI)**

**Title: Professional painting, outdoor brush/roller - CEPE\_PW\_06**

**This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.**

**General description of the process covered**



Outdoor painting by professionals with brush or roller.

This safe use information is linked to: SWED CEPE\_PW\_06

**Operational Conditions**

Outdoor use.

Maximum duration of individual exposure: covers daily use up to 8 hours, 225 days per year \*

<b>Risk Management Measures</b>			
<b>Contributing activity</b>	<b>Ventilation</b>	<b>Ventilation - air changes/hr</b>	
Preparation of material for application	Outdoors	3-5	
Loading of application equipment and handling of coated parts before curing	Outdoors	3-5	
Application	Outdoors	3-5	
Application equipment cleaning	Outdoors	3-5	
Waste management	Outdoors	3-5	
<b>Contributing activity</b>	<b>Respiratory</b>	<b>Eye</b> 	<b>Hands</b> 
Preparation of material for application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Loading of application equipment and handling of coated parts before curing	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Application equipment cleaning	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374
Waste management	None	Use eye protection according to EN 166	Wear suitable gloves tested to EN374

See Section 8 of this Safety Data Sheet for specifications.

In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

Disclaimer: The information in this Safe Use of Mixtures Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product. No liability is accepted for any damage, no matter of what kind, which is the direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.