



**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**SEAJET 028 DRAGON**

Product code: 628RR - Version 4 - Revision Date: 23-11-2021

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

PT21 - Antifouling paint.

**1.3. Details of the supplier of the safety data sheet**

Chugoku Paints B.V., Sluisweg 12, 4794 SW Heijningen, Po Box 73, 4793 ZH Fijnaart, The Netherlands, Tel.+31-167-526100, E-mail: msdsregistration@cmpeurope.eu

**1.4. Emergency telephone number**

National Poisons Information Service: England & Wales / NHS dial 111, Scotland NHS 24, <http://www.npis.org>  
N.Ireland, Contact your local GP or pharmacist during normal hours, [www.gpoutofhours.hscni.net](http://www.gpoutofhours.hscni.net) for GP services Out-of-Hours.

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP].**

Flam. Liq. 3 H226	Flammable liquid and vapour.
Acute Tox. 4 H302	Harmful if swallowed.
Acute Tox. 4 H332	Harmful if inhaled.
Skin Irrit. 2 H315	Causes skin irritation.
Eye Dam. 1 H318	Causes serious eye damage.
Repr.1 H360	May damage fertility or the unborn child.
Lact. H362	May cause harm to breast-fed children.
STOT RE 2 H373	May cause damage to organs through prolonged or repeated exposure.
Aquatic Acute 1 H400	Very toxic to aquatic life.
Aquatic Chronic 1 H410	Very toxic to aquatic life with long lasting effects.

**2.2. Label elements**



GHS02



GHS05



GHS07

**Hazard pictogram(s):**



GHS08



GHS09

**Signal word: Danger**

**Labelling according to Regulation (EC) No 1272/2008 [CLP]:**

**Hazard statement(s):**

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H332	Harmful if inhaled.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H360	May damage fertility or the unborn child.
H362	May cause harm to breast-fed children.
H373	May cause damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.

**Supplemental hazard information (EU): Not applicable.**



Product code: 628RR - Version 4 - Revision Date: 23-11-2021

**Precautionary statement(s)**

## Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260: Do not breathe vapours/spray.

P263: Avoid contact during pregnancy and while nursing.

P273: Avoid release to the environment.

P280: Wear protective gloves, protective clothing, eye protection, face protection.

## Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER or doctor.

P370+P378: In case of fire: Use alcohol resistant foam to extinguish.

P391: Collect spillage.

Storage &amp; Disposal: -

**Contains (EC 1272/2008 18.3(b)):**Reaction mass of Ethylbenzene and Xylene.  
Pyrethione zinc.

N-Butanol.

4-bromo-2-(4-chlorophenyl)-5- (trifluoromethyl)-1H-pyrrole-3- carbonitrile.

Chlorinated paraffins, C14-17 (52%).

Extended details regarding health and environment, see Section 11 &amp; 12.

**2.3. Other hazards**

This mixture contains Chlorinated paraffins, C14-17 (52%). The substance was assessed as PBT/vPvB.

Restricted to professional users.

Children shall be kept away until treated surfaces are dry.

Application, maintenance and repair activities shall be conducted within a contained area, on impermeable hard standing with bunding or on soil covered with an impermeable material to prevent losses and minimise emissions to the environment, and that any losses or waste shall be collected for reuse or disposal.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

Substances presenting a health or environmental hazard within the meaning of Regulation (EC) No. 1272/2008, assigned a Community workplace exposure limit, classified as PBT/vPvB or included in the Candidate List. (\*) For full text of H-statements, see SECTION 16.

Substance name	Identification number	% [weight]	Hazard statement Code(s) (*) / Hazard Class and Category Codes
Reaction Mass Of Ethylbenzene And Xylene.	EG-nr: 905-588-0 CAS-nr: - Index: - Reach#: 01-2119488216-32	12-16 %	H226 - Flam. Liq. 3 H304 - Asp. Tox. 1 H312 - Acute Tox. 4 H315 - Skin Irrit. 2 H319 - Eye Irrit. 2 H332 - Acute Tox. 4 H335 - STOT SE 3 H373 - STOT RE 2 SCL / M-factor / ATE: H312-ATE 1100mg/kg bw, H332-ATE 29mg/l
Zinc Oxide.	EG-nr: 215-222-5 CAS-nr: 1314-13-2 Index: 030-013-00-7 Reach#: 01-2119463881-32	5-10 %	H400 - Aquatic Acute 1 H410 - Aquatic Chronic 1
1-Methoxy-2-Propanol.	EG-nr: 203-539-1 CAS-nr: 107-98-2 Index: 603-064-00-3 Reach#: 01-2119457435-35	4-8 %	H226 - Flam. Liq. 3 H336 - STOT SE 3
Hydrocarbons, C10, Aromatics, <1% Naphthalene.	EG-nr: 918-811-1 CAS-nr: 1189173-42-9 Index: - Reach#: 01-2119463583-34	3-6 %	H304 - Asp. Tox. 1 H336 - STOT SE 3 H411 - Aquatic Chronic 2 EUH066
Pyrrhione Zinc.	EG-nr: 236-671-3 CAS-nr: 13463-41-7 Index: - Reach#: 01-2119511196-46	3-5 %	H360Df - Repr.1 H330 - Acute Tox. 2 H301 - Acute Tox. 3 H372 - STOT RE 1 H318 - Eye Dam. 1 H400 - Aquatic Acute 1 H410 - Aquatic Chronic 1 SCL / M-factor / ATE: H331-ATE 0.14 mg/L (Dust/Mist), H301-ATE 221mg/kg bw - M(ac)=1000 M(chr)=10
N-Butanol.	EG-nr: 200-751-6 CAS-nr: 71-36-3 Index: 603-004-00-6 Reach#: 01-2119484630-38	2-4 %	H226 - Flam. Liq. 3 H302 - Acute Tox. 4 H335 - STOT SE 3 H315 - Skin Irrit. 2 H318 - Eye Dam. 1 H336 - STOT SE 3 SCL / M-factor / ATE: H302-ATE 500
4-Bromo-2-(4-Chlorophenyl)-5-(Trifluoromethyl)-1H-Pyrrole-3- Carbonitrile.	EG-nr: 602-784-5 CAS-nr: 122454-29-9 Index: - Reach#: -	1-3 %	H300 - Acute Tox. 2 H330 - Acute Tox. 2 H311 - Acute Tox. 3 H372** - STOT RE 1 H373 - STOT RE 2 H400 - Aquatic Acute 1 H410 - Aquatic Chronic 1 SCL / M-factor / ATE: H300-ATE 28,7mg/kg bw, H311-ATE 520mg/kg bw, H330-ATE 0,25mg/l(Dust/Mist) - M(ac)=1000 M(chr)=100
Chlorinated Paraffins, C14-17 (52%).	EG-nr: 287-477-0 CAS-nr: 85535-85-9 Index: 602-095-00-X Reach#: 01-2119519269-33	1-2 %	H362 - Lact. H400 - Aquatic Acute 1 H410 - Aquatic Chronic 1 EUH066 SCL / M-factor / ATE: - M(ac)=100 M(chr)=100

**SECTION 4: First aid measures****4.1. Description of first aid measures**

Pay attention to your own safety! In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

**following inhalation:**

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

**following skin contact:**

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

**following eye contact:**

Remove contact lenses, if present and easy to do. Irrigate copiously with clean, fresh water, holding the eyelids apart for at least 15 minutes and seek immediate medical advice.

**following ingestion:**

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed****Potential acute symptoms and effects****following inhalation:**

No known significant effects or critical hazards.

**following skin contact:**

Causes skin irritation.

**following eye contact:**

Causes serious eye damage.

**following ingestion:**

Harmful if swallowed.

**Potential delayed symptoms and effects****following inhalation:**

No specific data.

**following skin contact:**

Adverse symptoms may include the following: irritation, redness

**following eye contact:**

Adverse symptoms may include the following: irritation, watering, redness

**following ingestion:**

No specific data.

**4.3. Indication of any immediate medical attention and special treatment needed****Notes to physician**

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**

No specific treatment.

**SECTION 5: Firefighting measures****5.1. Extinguishing media**

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist.

**Extinguishing media which must not be used for safety reasons:**

Water jet. Zincdust containing products should not be extinguished with water.

**5.2. Special hazards arising from the substance or mixture**

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. See Section 10.

**5.3. Advice for firefighters**

There is no one clothing material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Fire fighter's clothing conforming to European standard EN469 provides a basic level of protection for chemical incidents. Appropriate breathing apparatus may be required (Self-Contained Breathing Apparatus (SCBA)). Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel: Comply with company's emergency procedures. Exclude sources of ignition and ventilate the area. Use safety goggles or safety glasses, as well as any other appropriate personal protective equipment, at all times. Avoid breathing vapours. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Refer to protective measures listed in Sections 7 and 8.

For emergency responders: See Section 8 for information on appropriate personal protective equipment. See also the information: "For non-emergency personnel".

**6.2. Environmental precautions**

Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

**6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Place in a suitable container. Clean preferably with a detergent - avoid use of solvents.

**6.4. Reference to other sections**

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. No sparking tools should be used. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Smoking, eating and drinking should be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses. Isolate from sources of heat, sparks and open flame.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

**Information regarding fire and explosion hazard**

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in accordance with local regulations.

Product code: 628RR - Version 4 - Revision Date: 23-11-2021

**Notes on joint storage**

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

**Additional information on storage conditions**

Observe label precautions. Store between 0°C and 40°C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access.

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

**7.3. Specific end use(s)**

Application: Airless spray, Brush, Roller (See also Technical Data Sheet.) Spray: professional use only.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

Limits for occupational exposure and / or biological limit values		
	LIMIT VALUES TWA8h - STEL15 ppm-mg/m <sup>3</sup>	LIMIT VALUES TWA8h - STEL15 ppm-mg/m <sup>3</sup>
Reaction Mass Of Ethylbenzene And Xylene.	TWA8h - ppm / - mg/m <sup>3</sup>	TWA8h - ppm / - mg/m <sup>3</sup>
	STEL - ppm / - mg/m <sup>3</sup>	STEL15 - ppm / - mg/m <sup>3</sup>
	Annotations -	Notation -
Zinc Oxide.	TWA8h - ppm / - mg/m <sup>3</sup>	TWA8h - ppm / - mg/m <sup>3</sup>
	STEL - ppm / - mg/m <sup>3</sup>	STEL15 - ppm / - mg/m <sup>3</sup>
	Annotations -	Notation -
1-Methoxy-2-Propanol.	TWA8h 100 ppm / 375 mg/m <sup>3</sup>	TWA8h 100 ppm / 375 mg/m <sup>3</sup>
	STEL 150 ppm / 560 mg/m <sup>3</sup>	STEL15 150 ppm / 568 mg/m <sup>3</sup>
	Annotations Sk	Notation Skin
Hydrocarbons, C10, Aromatics, <1% Naphthalene.	TWA8h - ppm / - mg/m <sup>3</sup>	TWA8h - ppm / - mg/m <sup>3</sup>
	STEL - ppm / - mg/m <sup>3</sup>	STEL15 - ppm / - mg/m <sup>3</sup>
	Annotations -	Notation -
Pyrithione Zinc.	TWA8h - ppm / - mg/m <sup>3</sup>	TWA8h - ppm / - mg/m <sup>3</sup>
	STEL - ppm / - mg/m <sup>3</sup>	STEL15 - ppm / - mg/m <sup>3</sup>
	Annotations -	Notation -
N-Butanol.	TWA8h - ppm / - mg/m <sup>3</sup>	TWA8h - ppm / - mg/m <sup>3</sup>
	STEL 50 ppm / 154 mg/m <sup>3</sup>	STEL15 - ppm / - mg/m <sup>3</sup>
	Annotations Sk	Notation -
4-Bromo-2-(4-Chlorophenyl)-5- (Trifluoromethyl)-1H-Pyrrole-3-Carbonitrile.	TWA8h - ppm / - mg/m <sup>3</sup>	TWA8h - ppm / - mg/m <sup>3</sup>
	STEL - ppm / - mg/m <sup>3</sup>	STEL15 - ppm / - mg/m <sup>3</sup>
	Annotations -	Notation -
Chlorinated Paraffins, C14-17 (52%).	TWA8h - ppm / - mg/m <sup>3</sup>	TWA8h - ppm / - mg/m <sup>3</sup>
	STEL - ppm / - mg/m <sup>3</sup>	STEL15 - ppm / - mg/m <sup>3</sup>
	Annotations -	Notation -

U.K. - TWA=Time Weighted Average (8hr) - STEL=Short-term exposure limit (15-minute reference period) - H.S.E. Health and Safety Commission.

Europe - TWA = Time Weight Average (8hr) - Measured or calculated in relation to a reference period of 8 hours time-weighted average (TWA) - STEL = Short-term exposure limit - A limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified - SCOEL

Annotations / Notations:

BMGVs: Biological monitoring guidance values.

Carc: Capable of causing cancer and/or heritable genetic damage.

Inh.: Inhalable fraction.

Resp.: Respirable fraction.

Sen: Capable of causing occupational asthma.

Sk: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

Skin: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin.

**DNEL**

DNEL - Not available.

**PNEC**

PNEC - Not available.

## 8.2. Exposure controls

### Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

### Individual protection measures, such as personal protective equipment

#### Personal Protection

##### Respiratory protection



If workers could be exposed to concentrations above the exposure limit they should use a respirator to EN 140, fitted with a filter suitable for both particulates and vapours to EN14387, with an assigned protection factor of at least 10 (e.g. A2P3).

Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

##### Hand protection






There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. At repeated or prolonged contact; use gloves tested according to EN 374. Viton-gloves offer good protection for intense contact with most solvents, e.g. complete immersion in solvent.

Nitrile gloves offer good protection during spray application. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. The breakthrough time must be greater than the end use time of the product. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred. Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing. USE PE gloves as under gloves for difficult situations like for instance: high exposure, unknown composition or unknown properties of the chemicals.

<b>Gloves for repeated or prolonged exposure (Permeation breakthrough times &gt; 480 min) - High Protection:</b>		
<b>Material:</b>	<b>Minimum Thickness:</b>	<b>Chemical resistance:</b>
Polyethylene (PE) Gloves	0,062mm	High
<b>Gloves for repeated or prolonged exposure (Permeation breakthrough times 240 - 480 min) - High Protection:</b>		
<b>Material:</b>	<b>Minimum Thickness:</b>	<b>Chemical resistance:</b>
Polyethylene (PE) Gloves	0,062mm	High
Butyl Viton Gloves	0,70mm	High
<b>Gloves for repeated or prolonged exposure (Permeation breakthrough times 120-240 min) - Medium Protection:</b>		
<b>Material:</b>	<b>Minimum Thickness:</b>	<b>Chemical resistance:</b>
Polyethylene (PE) Gloves	0,062mm	High
Butyl Viton Gloves	0,70mm	High
<b>Gloves for repeated or prolonged exposure (Permeation breakthrough times 60 - 120 min) - Medium Protection:</b>		
<b>Material:</b>	<b>Minimum Thickness:</b>	<b>Chemical resistance:</b>
Polyethylene (PE) Gloves	0,062mm	High
PVA Gloves	0,2-0,3mm	High
Butyl Viton Gloves	0,70mm	High

Product code: 628RR - Version 4 - Revision Date: 23-11-2021

<b>Gloves for short term exposure / splash protection (Permeation breakthrough times 30 - 60 min):</b>		
<b>Material:</b>	<b>Minimum Thickness:</b>	<b>Chemical resistance:</b>
Polyethylene (PE) Gloves	0,062mm	High
PVA Gloves	0,2-0,3mm	High
Butyl Viton Gloves	0,70mm	High
Nitrile Gloves	0,31mm	High
<b>Gloves for short term exposure / splash protection (Permeation breakthrough times 10 - 30 min):</b>		
<b>Material:</b>	<b>Minimum Thickness:</b>	<b>Chemical resistance:</b>
Polyethylene (PE) Gloves	0,062mm	High
PVA Gloves	0,2-0,3mm	High
Butyl Viton Gloves	0,70mm	High
Neoprene Gloves	<0,4mm	High
Nitrile Gloves	0,175mm	High
<b>Non suitable Gloves - non exhaustive list (Permeation breakthrough times &lt; 10 min):</b>		
<b>Material:</b>	<b>Thickness (or less):</b>	
Natural Rubber Gloves	0,75mm	
Nitrile Gloves	-	
Neoprene Gloves	0,75mm	
Butyl Gloves	0,50mm	

-  Eye/face protection  
Use safety eyewear tested according to EN 166 designed to protect against splash of liquids.
-  Skin protection  
Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.
-  Environmental exposure controls  
Do not allow to enter drains or water courses.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**(a) Physical state**

Liquid

**(b) Colour**

Diverse.

**(c) Odour**

Typical aromatic odour.

**(d) Melting point/freezing point**

Not applicable due to nature of the product.

**(e) Boiling point or initial boiling point and boiling range**

Not applicable due to nature of the product. Lowest Boiling Point: 1-methoxy-2-propanol. - 117°C

**(f) Flammability**

Vapours are ignitable. See Flash point (h).

**(g) Lower and upper explosion limit**

The product itself is not explosive, but the formation of an explosive mixture of vapour or dust with air is possible.

Reaction Mass Of Ethylbenzene And Xylene.	1.0-7.0%
Zinc Oxide.	Not applicable.
1-Methoxy-2-Propanol.	1.9-13.1%
Hydrocarbons, C10, Aromatics, <1% Naphthalene.	Not available.



Product code: 628RR - Version 4 - Revision Date: 23-11-2021

**(g) Lower and upper explosion limit**

Pyrithione Zinc.	Not applicable.
N-Butanol.	1.4-11.3%
4-Bromo-2-(4-Chlorophenyl)-5- (Trifluoromethyl)-1H-Pyrrole-3- Carbonitrile.	Not available.
Chlorinated Paraffins, C14-17 (52%).	Not available.

**(h) Flash point**

25°C - Method: ASTM D3278-96 (Re-appr.2004)

**(i) Auto-ignition temperature**

Not applicable due to nature of the product.

Lowest auto ignition temperature: 1-methoxy-2-propanol. - 287°C

**(j) Decomposition temperature**

Not applicable due to nature of the product.

**(k) pH**

Not applicable due to nature of the product. Mixture is non-soluble (in water).

**(l) Kinematic viscosity**

457 mm<sup>2</sup>/s @40°C - Method: ISO3219

Non-Newtonian liquid - thixotropic behaviour.

**(m) Solubility**

Not Soluble (in water).

**(n) Partition coefficient n-octanol/water (log value)**

Not applicable due to nature of the product.

**(o) Vapour pressure**

Reaction Mass Of Ethylbenzene And Xylene.	8.0 mbar
Zinc Oxide.	Not applicable.
1-Methoxy-2-Propanol.	11.6 mbar
Hydrocarbons, C10, Aromatics, <1% Naphthalene.	1 Kpa
Pyrithione Zinc.	Not available.
N-Butanol.	5,6 mbar
4-Bromo-2-(4-Chlorophenyl)-5- (Trifluoromethyl)-1H-Pyrrole-3- Carbonitrile.	1,9x10-8 Pa
Chlorinated Paraffins, C14-17 (52%).	0,00027hPa

**(p) Density and/or relative density**

Relative density 1,51-1,55 @ 20°C - Method: ASTM D1475-98

**(q) Relative vapour density**

1-2 @ 20°C - Method: Calculated.

**(r) Particle characteristics**

Not applicable due to nature of the product.

**9.2. Other information**

Information with regard to physical hazard classes

No relevant information.

Other safety characteristics

No relevant information.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No specific test data related to reactivity available for this product or its ingredients.

### 10.2. Chemical stability

Stable under recommended storage and handling conditions (see Section 7).

### 10.3. Possibility of hazardous reactions

In combination with oxidizing agents, strongly alkaline and strongly acid materials, exothermic reactions and/or explosive reactions may occur or toxic vapours may arise.

### 10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

### 10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials.

### 10.6. Hazardous decomposition products

Carbon monoxide and dioxide, smoke, oxides of nitrogen, hydrochloric acid, etc.

## SECTION 11: Toxicological information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Substance name

Reaction Mass Of Ethylbenzene And Xylene. - LD50 Oral - >2000 mg/kg, Rat - LD50 Dermal - >2000 mg/kg, Rat - LC50 Inhalation - 29 mg/lRat,4h

Zinc Oxide. - LD50 Oral - >5000 mg/kg, Rat - LD50 Dermal - Not available. - LC50 Inhalation - >5700 mg/m3Rat,4h

1-Methoxy-2-Propanol. - LD50 Oral - 4016 mg/kg, Rat - LD50 Dermal - >13300 mg/kg, Rabbit - LC50 Inhalation - 54,6 mg/lRat,4h

Hydrocarbons, C10, Aromatics, <1% Naphthalene. - LD50 Oral - Not available. - LD50 Dermal - Not available. - LC50 Inhalation - Not available.

Pyriithione Zinc. - LD50 Oral - 269 mg/kg, Rat - LD50 Dermal - >2000 mg/kg, Rat - LC50 Inhalation - 1,03 mg/lRat,4h

N-Butanol. - LD50 Oral - >2000 mg/kg, Rat - LD50 Dermal - >2000 mg/kg, Rabbit - LC50 Inhalation - >17,76 mg/lRat,4h

4-Bromo-2-(4-Chlorophenyl)-5-(Trifluoromethyl)-1H-Pyrrole-3- Carbonitrile. - LD50 Oral - 28,7 mg/kg, Rat - LD50 Dermal - 520-750mg/kg, Guinea pig - LC50 Inhalation - <0,25 mg/lRat,4h

Chlorinated Paraffins, C14-17 (52%). - LD50 Oral - >2000 mg/kg (bw), Rat - LD50 Dermal - 4000 mg/kg, Rat - LC50 Inhalation - Not available.

Product code: 628RR - Version 4 - Revision Date: 23-11-2021

**Conclusion/Summary on mixture****Acute toxicity:**

ATEmix (oral) : No specific data.  
ATEmix (Dermal) : No specific data.  
ATEmix (Inhalation) : No specific data.

**Skin corrosion/irritation:**

Conclusion/Summary on mixture: Causes skin irritation.

Method: Additivity approach, No testdata available.

**Serious eye damage/irritation:**

Conclusion/Summary on mixture: Causes serious eye damage.

Method: Additivity approach, no testdata available.

**Respiratory or skin sensitisation:**

Conclusion/Summary on mixture

Respiratory sensitization Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

Skin sensitization Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

**Germ cell mutagenicity:**

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

**Carcinogenicity:**

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

**Reproductive toxicity:**

Conclusion/Summary on mixture: May damage fertility or the unborn child. Method: Concentration Limit, no testdata available.

**STOT - single exposure:**

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

**STOT - repeated exposure:**

Conclusion/Summary on mixture: May cause damage to organs through prolonged or repeated exposure. Method: Concentration Limit, no testdata available.

**Aspiration hazard:**

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met.

Justification: Additivity approach / Kinematic viscosity: 457 mm<sup>2</sup>/s @40°C - Measured

**Information on likely routes of exposure**

Inhalation: Exposure to vapours may cause a health hazard. Serious effects may be delayed following exposure.

Ingestion: Harmful if swallowed.

Skin exposure: Causes skin irritation.

Eye exposure: Causes serious eye damage.

**Symptoms related to the physical, chemical and toxicological characteristics**

Inhalation: No specific data.

Ingestion: No specific data.

Skin exposure: Adverse symptoms may include the following: irritation, redness.

Eye exposure: Adverse symptoms may include the following: irritation, watering, redness.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Short term exposure:**

Potential immediate effects: No specific data.

Potential delayed effects: No specific data.

**Long term exposure:**

Potential immediate effects: No specific data.

Potential delayed effects: No specific data.

Product code: 628RR - Version 4 - Revision Date: 23-11-2021

**Potential chronic health effects:**

Conclusion/Summary on mixture

General:	No known significant effects or critical hazards.
Carcinogenicity:	No known significant effects or critical hazards.
Mutagenicity:	No known significant effects or critical hazards.
Teratogenicity:	No known significant effects or critical hazards.
Developmental effects:	No known significant effects or critical hazards.
Fertility effects:	No known significant effects or critical hazards.
Other information:	No relevant information.

**11.2 Information on other hazards**

Endocrine disrupting properties

No relevant information.

Other information

No relevant information.

**SECTION 12: Ecological information**

There are no data available on the mixture itself. Do not allow to enter drains or water courses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and classified for eco-toxicological hazards accordingly.

**12.1. Toxicity**

**Substance name - Species - Exposure - Results**

Reaction Mass Of Ethylbenzene And Xylene. Acute (short-term) toxicity: Fish: LC50/96h - 2.6 mg/l, Crustacea: EC50/48h 1-10 mg/l (Daphnia magna), Algae/aquatic plants: EC50/72h 2.2 mg/L (Pseudokirchneriella subcapitata), Other organisms: Not available. Chronic (long-term) toxicity: Fish: NOEC >1.3 mg/L (Salmo gairdneri), Crustacea: NOEC 0.96mg/L, Algae/aquatic plants: NOEC 0.44mg/L, Other organisms: Not available.

Zinc Oxide. Acute (short-term) toxicity: Fish: LC50 0,169 mg Zn/l (Oncorhynchus Mykiss), Crustacea: EC50/48h - 0.413 mg/l (Ceriodaphnia dubia), Algae/aquatic plants: EC50/72h - 0,137 mg/l (Selenastrum Capricornutum), Other organisms: Not available. Chronic (long-term) toxicity: Fish: NOEC 0.025 mg Zn/l, Crustacea: NOEC 82 ug/l, Algae/aquatic plants: NOEC 19 ug/l (Pseudokirchneriella subcapitata), Other organisms: Not available.

1-Methoxy-2-Propanol. Acute (short-term) toxicity: Fish: LC50/96h 6812 mg/l (Leuciscus Idus), Crustacea: EC50/48h 23300 mg/l (Daphnia magna), Algae/aquatic plants: EC50/7d >1000 mg/L (Pseudokirchneriella subcapitata), Other organisms: Not available. Chronic (long-term) toxicity: Fish: Not available., Crustacea: Not available., Algae/aquatic plants: Not available., Other organisms: Not available.

Hydrocarbons, C10, Aromatics, <1% Naphthalene. Acute (short-term) toxicity: Fish: LC50/96h >=2<=5 mg/l (Oncorhynchus mykiss), Crustacea: EC50/48h >=3<=10 mg/l (Daphnia magna), Algae/aquatic plants: EC50/72h 11 mg/l (Pseudokirchneriella Subcapitata), Other organisms: Not available. Chronic (long-term) toxicity: Fish: NOELR 0.441 mg/L, Crustacea: NOELR 0.771 mg/L, Algae/aquatic plants: Not available., Other organisms: Not available.

Pyrethione Zinc. Acute (short-term) toxicity: Fish: LC50 /96h - 0,0026 mg/l (Pimephales promelas), Crustacea: EC50/48h - 0,0082 mg/L (Daphnia magna), Algae/aquatic plants: EC50/120h - 0,0012 mg/l (Skeletonema costatum), Other organisms: Not available. Chronic (long-term) toxicity: Fish: Not available., Crustacea: Not available., Algae/aquatic plants: Not available., Other organisms: Not available.

N-Butanol. Acute (short-term) toxicity: Fish: LC50/96h 1376 mg/l (Pimephales promelas), Crustacea: EC50/48h 1328 mg/l (Daphnia magna), Algae/aquatic plants: EC50/96h 225 mg/l (Selenastrum capricornutum), Other organisms: Not available. Chronic (long-term) toxicity: Fish: Not available., Crustacea: NOEC 4,1 mg/l, Algae/aquatic plants: NOEC 129 mg/L, Other organisms: Not available.

4-Bromo-2-(4-Chlorophenyl)-5-(Trifluoromethyl)-1H-Pyrrole-3- Carbonitrile. Acute (short-term) toxicity: Fish: LC50/96h 0,013 mg/l (Oncorhynchus mykiss), Crustacea: EC50/96h 0,0066 mg/l (Crassostrea virginica), Algae/aquatic plants: Not available., Other organisms: Not available. Chronic (long-term) toxicity: Fish: NOEC 0,001mg/l, Crustacea: NOEC 0,0029mg/l, Algae/aquatic plants: Not available., Other organisms: Not available.

Chlorinated Paraffins, C14-17 (52%). Acute (short-term) toxicity: Fish: LC/96h >5000 mg/l (Alburnus alburnus), Crustacea: EC50/48h 0,006 mg/l (Daphnia magna), Algae/aquatic plants: EC50/96h >3,2 mg/l (Selenastrum capricornutum), Other organisms: Not available. Chronic (long-term) toxicity: Fish: NOEC 125 ug/l, Crustacea: NOEC 0.01 mg/L, Algae/aquatic plants: NOEC 0.1 mg/L, Other organisms: Not available.

Product code: 628RR - Version 4 - Revision Date: 23-11-2021

### 12.2. Persistence and degradability

#### Substance name

Reaction Mass Of Ethylbenzene And Xylene. - Readily biodegradable.

Zinc Oxide. - Readily biodegradable.

1-Methoxy-2-Propanol. - Readily biodegradable.

Hydrocarbons, C10, Aromatics, <1% Naphthalene. - Inherently biodegradable.

Pyrithione Zinc. - Inherently biodegradable.

N-Butanol. - Readily biodegradable.

4-Bromo-2-(4-Chlorophenyl)-5- (Trifluoromethyl)-1H-Pyrrole-3- Carbonitrile. - Readily biodegradable.

Chlorinated Paraffins, C14-17 (52%). - Readily biodegradable.

### 12.3. Bioaccumulative potential

#### Substance name

Reaction Mass Of Ethylbenzene And Xylene.

log Kow

BCF

3,1

25,9

Zinc Oxide.

Not available.

Not available.

1-Methoxy-2-Propanol.

-0,43

Not available.

Hydrocarbons, C10, Aromatics, <1% Naphthalene.

Not available.

Not available.

Pyrithione Zinc.

0,93

1,4

N-Butanol.

0,88

3,16

4-Bromo-2-(4-Chlorophenyl)-5- (Trifluoromethyl)-1H-Pyrrole-3- Carbonitrile.

3,47

3,2

Chlorinated Paraffins, C14-17 (52%).

7

<2000 L/kg

### 12.4. Mobility in soil

Soil/water partition coefficient (KOC)

: Not available.

Mobility

: No relevant information.

### 12.5. Results of PBT and vPvB assessment

This mixture contains Chlorinated paraffins, C14-17 (52%). The substance was assessed as PBT/vPvB.

### 12.6. Endocrine disrupting properties

No relevant information.

### 12.7. Other adverse effects

No relevant information.

## SECTION 13: Disposal considerations






### 13.1. Waste treatment methods

Product / Packaging disposal: Dispose of containers contaminated by the product in accordance with local or national legal provisions. The European Waste Catalogue (2000/532/EC) classification of this product. Waste codes / waste designations according to LoW: 07 04 99 Wastes not otherwise specified. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information contact your local waste authority. Waste should not be disposed of by release to sewers. Using information provided in this safety data sheet, advice should be obtained from the local waste authority on the classification of empty containers.

Containers which are not properly cleaned may contain (highly) flammable or explosive vapours.

Special precautions: Use appropriate protective equipment for the removal and / or disposal of this product.

**SECTION 14: Transport information**

	ADR / RID / ADN	IMDG-Code	IATA
14.1. UN number or ID number	UN 1263	UN 1263	UN 1263
14.2. UN			
	PAINT	PAINT	PAINT
14.3. Transport hazard class(es)	3	3	3
Label(s)			
14.4. Packing group	III	III	III
14.5. Environmental hazards	Yes Environmental hazardous substances (aquatic environment) 	Yes Marine Pollutant: Yes  Marine Pollutant substance(s): Zinc Oxide., Pyrethione zinc.	No
Additional information	Hazard Identification Number No.: 30	Emergency Schedule Number (EmS): F-E, S-E	

**14.6. Special precautions for user**

Transport within the user's premises:  
 Always transport in closed containers that are upright and secure.  
 Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7. Maritime transport in bulk according to IMO instruments**

Not applicable.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

The information in this Safety Data Sheet is required pursuant to Annex II to regulation (EC) No 1907/2006 and its amendments.  
 The provisions of the Health and Safety at Work etc. Act [and the Control of Substances Hazardous to Health Regulations] apply to the use of this product at work.  
 The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.



Product code: 628RR - Version 4 - Revision Date: 23-11-2021

Seveso category (DIRECTIVE 2012/18/EU): P5c - E1 This product may add to the calculation for determining whether a site is within scope of the Seveso Directive on major accident hazards.

\* Active substance: Pyrithione Zinc. / CAS 13463-41-7 32g/kg.  
4-Bromo-2-(4-Chlorophenyl)-5- (Trifluoromethyl)-1H-Pyrrole-3- Carbonitrile. / CAS 122454-29-9 20g/kg.

\* Note: Values given are based on theoretical calculations. Actual values could differ.

## 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008

#### [CLP]:

H226	Measured
H302	Summation method (ATE)
H332	Summation method (ATE)
H315	Additivity approach
H318	Additivity approach
H360	Concentration limit
H362	Concentration limit
H373	Concentration limit
H400	Summation method
H410	Summation method

#### Abbreviations and acronyms:

ADN	: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	: Acute Toxicity Estimate
BCF	: Bioconcentration factor
CLP	: Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DNEL	: Derived No Effect Level
IATA	: International Air Transport Association
IMDG-Code	: International Maritime Dangerous Goods
Kow	: octanol-water partition coefficient
LC50	: Lethal Concentration to 50 % of a test population
LD50	: Lethal Dose to 50% of a test population (Median Lethal Dose)
PBT	: Persistent, Bioaccumulative and Toxic substance
PNEC	: Predicted No Effect Concentration(s)
RID	: Regulations concerning the International Carriage of Dangerous Goods by Rail
STOT	: Specific Target Organ Toxicity
vPvB	: Very Persistent and Very Bioaccumulative



Product code: 628RR - Version 4 - Revision Date: 23-11-2021

**Full text of Hazard Statements appearing in Section 3.2.:**

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H300	Fatal if swallowed.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H360Df	May damage the unborn child. Suspected of damaging fertility.
H362	May cause harm to breast-fed children.
H372	Causes damage to organs through prolonged or repeated exposure.
H372**	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Amendments: 24-11-2021, §2,3,8,9,11,12&amp;16

This product does not contain organotin compounds acting as biocides and complies with the "International convention on the control of harmful Anti-fouling systems on ships as adopted by IMO in october 2001 (IMO document AFS/CONF/26)".

The information of this SDS is based on the present state of our knowledge and on current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.