

## SECTION 1: Identification of the substance/mixture and of the company/undertaking



### 1.1. Product identifier

#### SEAJET 132 POLYURETHANE TOPCOAT BASE

Product code: 573PZ - Version 2.2 - Revision Date: 21-12-2015

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Paint and/or related product.

### 1.3. Details of the supplier of the safety data sheet

Chugoku Paints B.V., Sluisweg 12, 4794 SW Heijningen, Po Box 73, 4793 ZH Fijnaart, The Netherlands, Tel.+31-167-526100, E-mail: msdsregistration@cmpeurope.eu

### 1.4. Emergency telephone number

National Poisons Information Center: Accident and emergency unit Mater Dei hospital, Emergency telephone number Tel. 112

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 H226 Flammable liquid and vapour.  
Skin Irrit. 2 H315 Causes skin irritation.

### 2.2. Label elements



GHS02



GHS07

Hazard pictogram(s):

Signal word: Warning

#### Labelling according to Regulation (EC) No 1272/2008 [CLP]:

##### Hazard statement(s):

H226 Flammable liquid and vapour.  
H315 Causes skin irritation.

#### Supplemental hazard information (EU):

EUH208 Contains Reaction Mass Of A-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl)Propionyl- $\Omega$ -Hydroxypoly (Oxyethylene) And A-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl)Propionyl- $\Omega$ -3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl) Propionyloxypoly(Oxyethylene)., Bis (1,2,2',6,6'-Pentamethyl-4-



Product code: 573PZ - Version 2.2 - Revision Date: 21-12-2015

**Precautionary statement(s)**

## Prevention:

- P101: If medical advice is needed, have product container or label at hand.
- P102: Keep out of reach of children.
- P271: Use only outdoors or in a well-ventilated area.
- P280: Wear protective gloves, protective clothing, eye protection, face protection.

## Response:

- P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.
- P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

Storage &amp; Disposal: -

**Contains (EC 1272/2008 18.3(b)):** -

Extended details regarding health and environment, see Section 11 &amp; 12.

**2.3. Other hazards**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.



Product code: 573PZ - Version 2.2 - Revision Date: 21-12-2015

**SECTION 3: Composition/information on ingredients**


**3.2. Mixtures**

Substances presenting a health or environmental hazard within the meaning of Regulation (EC) No. 1272/2008, assigned a Community workplace exposure limit, classified as PBT/vPvB or included in the Candidate List. (\*) For full text of H-statements, see SECTION 16.


| Substance name  | Identification number    | % [weight] | Hazard statement Code(s) (*) / Hazard Class and Category Codes |
|---|--------------------------|------------|--|
| 2-Methoxy-1-Methylethyl Acetate.  | EG-nr: 203-603-9         | 10-25 %    | H226 - Flam. Liq. 3  |
|   | CAS-nr: 108-65-6         |            | H336 - STOT SE 3   |
|   | Index: 607-195-00-7      |            |  |
|   | Reach#: 01-2119475791-29 |            |  |
|   |                          |            |  |
| Xylene.   | EG-nr: 215-535-7         | 10-25 %    | H226 - Flam. Liq. 3  |
|   | CAS-nr: 1330-20-7        |            | H332 - Acute Tox. 4  |
|   | Index: 601-022-00-9      |            | H312 - Acute Tox. 4  |
|   | Reach#: 01-2119488216-32 |            | H315 - Skin Irrit. 2   |
|   |                          |            | SCL / M-factor / ATE: H312-ATE 1100, H332-ATE 29mg/l(Vap)      |
| Ethyl Methyl Ketone.  | EG-nr: 201-159-0         | ≤2,5 %     | H225 - Flam. Liq. 2  |
|   | CAS-nr: 78-93-3          |            | H319 - Eye Irrit. 2  |
|   | Index: 606-002-00-3      |            | H336 - STOT SE 3   |
|   | Reach#: 01-2119457290-43 |            | EUH066   |
|   |                          |            |  |
| Ethylbenzene.   | EG-nr: 202-849-4         | ≤2,5 %     | H225 - Flam. Liq. 2  |
|   | CAS-nr: 100-41-4         |            | H304 - Asp. Tox. 1   |
|   | Index: 601-023-00-4      |            | H332 - Acute Tox. 4  |
|   | Reach#: 01-2119489370-35 |            | H373-(**) - STOT RE 2  |
|   |                          |            | SCL / M-factor / ATE: H332-ATE 17,6mg/l(Vap)                   |
| Reaction Mass Of A-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl)Propionyl-Ω-Hydroxypoly (Oxyethylene) And A-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl)Propionyl-Ω-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl) Propionyloxypoly(Oxyethylene). | EG-nr: 400-830-7         | ≤0,5 %     | H317 - Skin Sens. 1  |
|   | CAS-nr: -                |            | H411 - Aquatic Chronic 2                                       |
|   | Index: 607-176-00-3      |            |  |
|   | Reach#: 01-0000015075-76 |            |  |
|   |                          |            |  |
| Bis (1,2,2',6,6'-Pentamethyl-4-Piperidyl)Sebacate.  | EG-nr: 915-687-0         | ≤0,5 %     | H317-(1A) - Skin Sens. 1A                                      |
|   | CAS-nr: 41556-26-7       |            | H400 - Aquatic Acute 1   |
|   | Index: -                 |            | H410 - Aquatic Chronic 1                                       |
|   | Reach#: 01-2119491304-40 |            |  |
|   |                          |            |  |




Product code: 573PZ - Version 2.2 - Revision Date: 21-12-2015

**SECTION 4: First aid measures****4.1. Description of first aid measures**


Pay attention to your own safety! In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

**following inhalation:**


Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

**following skin contact:**

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

**following eye contact:**

Remove contact lenses, if present and easy to do. Irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

**following ingestion:**

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed****Potential acute symptoms and effects****following inhalation:**

No known significant effects or critical hazards.

**following skin contact:**

Causes skin irritation.

**following eye contact:**

No known significant effects or critical hazards.

**following ingestion:**

No known significant effects or critical hazards.

**Potential delayed symptoms and effects****following inhalation:**

No specific data.

**following skin contact:**

May cause an allergic skin reaction.

**following eye contact:**

Adverse symptoms may include the following: irritation, watering, redness

**following ingestion:**

No specific data.

**4.3. Indication of any immediate medical attention and special treatment needed****Notes to physician**

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**

No specific treatment.



Product code: 573PZ - Version 2.2 - Revision Date: 21-12-2015

**SECTION 5: Firefighting measures****5.1. Extinguishing media**

Recommended: alcohol resistant foam, CO2, powders.

**Extinguishing media which must not be used for safety reasons:**

Water jet. Zinc dust containing products should not be extinguished with water.

**5.2. Special hazards arising from the substance or mixture**

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. See Section 10.

**5.3. Advice for firefighters**

There is no one clothing material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Fire fighter's clothing conforming to European standard EN469 provides a basic level of protection for chemical incidents. Appropriate breathing apparatus may be required (Self-Contained Breathing Apparatus (SCBA)). Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel: Comply with company's emergency procedures. Exclude sources of ignition and ventilate the area. Use safety goggles or safety glasses, as well as any other appropriate personal protective equipment, at all times. Avoid breathing vapours. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Refer to protective measures listed in Sections 7 and 8.

For emergency responders: See Section 8 for information on appropriate personal protective equipment. See also the information: "For non-emergency personnel".

**6.2. Environmental precautions**

Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

**6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Place in a suitable container. Clean preferably with a detergent - avoid use of solvents.

**6.4. Reference to other sections**

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. No sparking tools should be used. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Smoking, eating and drinking should be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses. Isolate from sources of heat, sparks and open flame.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

**Information regarding fire and explosion hazard**

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in accordance with local regulations.



Product code: 573PZ - Version 2.2 - Revision Date: 21-12-2015

Notes on joint storage: Store away from oxidising agents, from strongly alkaline and strongly acid materials.

**Additional information on storage conditions**

Observe label precautions. Store between 0°C and 40°C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

**7.3. Specific end use(s)**

Application: Air spray, Brush, Roller (See also Technical Data Sheet.)

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

| Limits for occupational exposure and / or biological limit values  |   |   |
|--|---|---|
|  | LIMIT VALUES TWA8h - STEL15 ppm-mg/m <sup>3</sup> | LIMIT VALUES TWA8h - STEL15 ppm-mg/m <sup>3</sup> |
| 2-Methoxy-1-Methylethyl Acetate.   | TWA8h 50 ppm / 275 mg/m <sup>3</sup>              | TWA8h 50 ppm / 275 mg/m <sup>3</sup>              |
|  | STEL 100 ppm / 550 mg/m <sup>3</sup>              | STEL15 100 ppm / 550 mg/m <sup>3</sup>            |
|  | Notations Skin                                    | Notation Skin                                     |
| Xylene.  | TWA8h 50 ppm / 221 mg/m <sup>3</sup>              | TWA8h 50 ppm / 221 mg/m <sup>3</sup>              |
|  | STEL 100 ppm / 442 mg/m <sup>3</sup>              | STEL15 100 ppm / 442 mg/m <sup>3</sup>            |
|  | Notations Skin                                    | Notation Skin                                     |
| Ethyl Methyl Ketone.   | TWA8h 200 ppm / 600 mg/m <sup>3</sup>             | TWA8h 200 ppm / 600 mg/m <sup>3</sup>             |
|  | STEL 300 ppm / 900 mg/m <sup>3</sup>              | STEL15 300 ppm / 900 mg/m <sup>3</sup>            |
|  | Notations -                                       | Notation -  |
| Ethylbenzene.  | TWA8h 100 ppm / 442 mg/m <sup>3</sup>             | TWA8h 100 ppm / 442 mg/m <sup>3</sup>             |
|  | STEL 200 ppm / 884 mg/m <sup>3</sup>              | STEL15 200 ppm / 884 mg/m <sup>3</sup>            |
|  | Notations Skin                                    | Notation Skin                                     |
| Reaction Mass Of A-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl)Propionyl-Ω-Hydroxypoly (Oxyethylene) And A-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl)Propionyl-Ω-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl) | TWA8h - ppm / - mg/m <sup>3</sup>                 | TWA8h - ppm / - mg/m <sup>3</sup>                 |
|  | STEL - ppm / - mg/m <sup>3</sup>                  | STEL15 - ppm / - mg/m <sup>3</sup>                |
|  | Notations -                                       | Notation -  |
| Bis (1,2,2',6,6'-Pentamethyl-4-Piperidyl)Sebacate.   | TWA8h - ppm / - mg/m <sup>3</sup>                 | TWA8h - ppm / - mg/m <sup>3</sup>                 |
|  | STEL - ppm / - mg/m <sup>3</sup>                  | STEL15 - ppm / - mg/m <sup>3</sup>                |
|  | Notations -                                       | Notation -  |

Malta - TWA=Time Weighted Average (8hr) - STEL=Short-term exposure limit (15-minute reference period) - Protection of the Health and Safety of Workers from the Risks related to Chemical Agents at Work Regulations.

Europe - TWA = Time Weight Average (8hr) - Measured or calculated in relation to a reference period of 8 hours time-weighted average (TWA) - STEL = Short-term exposure limit - A limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified - SCOEL

Notation(s):

(1): Short-term exposure limit value in relation to a reference period of 1 minute.

Inh.: Inhalable fraction.

Resp.: Respirable fraction.

Skin: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin.

DNEL - Not available.

PNEC - Not available.

**8.2. Exposure controls**

**Appropriate engineering controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.



Product code: 573PZ - Version 2.2 - Revision Date: 21-12-2015

**Individual protection measures, such as personal protective equipment**

**Personal Protection**

Respiratory protection



If workers could be exposed to concentrations above the exposure limit they should use a respirator to EN 140, fitted with a filter suitable for both particulates and vapours to EN14387, with an assigned protection factor of at least 10 (e.g. A2P3).

Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Hand protection



There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. At repeated or prolonged contact; use gloves tested according to EN 374.

Viton-gloves offer good protection for intense contact with most solvents, e.g. complete immersion in solvent. Nitrile gloves offer good protection during spray application. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. The breakthrough time must be greater than the end use time of the product. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

|  |                           |                             |
|--|---------------------------|-----------------------------|
| <b>Gloves for repeated or prolonged exposure (Permeation breakthrough times &gt; 480 min) - High Protection:</b>   |                           |                             |
| <b>Material:</b>   | <b>Minimum Thickness:</b> | <b>Chemical resistance:</b> |
|  |                           |                             |
| <b>Gloves for repeated or prolonged exposure (Permeation breakthrough times 240 - 480 min) - High Protection:</b>  |                           |                             |
| <b>Material:</b>   | <b>Minimum Thickness:</b> | <b>Chemical resistance:</b> |
|  |                           |                             |
| <b>Gloves for repeated or prolonged exposure (Permeation breakthrough times 120-240 min) - Medium Protection:</b>  |                           |                             |
| <b>Material:</b>   | <b>Minimum Thickness:</b> | <b>Chemical resistance:</b> |
|  |                           |                             |
| <b>Gloves for repeated or prolonged exposure (Permeation breakthrough times 60 - 120 min) - Medium Protection:</b> |                           |                             |
| <b>Material:</b>   | <b>Minimum Thickness:</b> | <b>Chemical resistance:</b> |
|  |                           |                             |
| <b>Gloves for short term exposure / splash protection (Permeation breakthrough times 30 - 60 min):</b>             |                           |                             |
| <b>Material:</b>   | <b>Minimum Thickness:</b> | <b>Chemical resistance:</b> |
|  |                           |                             |



Product code: 573PZ - Version 2.2 - Revision Date: 21-12-2015

|  |                             |                             |
|--|-----------------------------|-----------------------------|
| <b>Gloves for short term exposure / splash protection (Permeation breakthrough times 10 - 30 min):</b> |                             |                             |
| <b>Material:</b>   | <b>Minimum Thickness:</b>   | <b>Chemical resistance:</b> |
|  |                             |                             |
| <b>Non suitable Gloves - non exhaustive list (Permeation breakthrough times &lt; 10 min):</b>          |                             |                             |
| <b>Material:</b>   | <b>Thickness (or less):</b> |                             |
|  |                             |                             |

Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing. USE PE gloves as under gloves for difficult situations like for instance: high exposure, unknown composition or unknown properties of the chemicals.



Eye/face protection

Use safety eyewear tested according to EN 166 designed to protect against splash of liquids.



Skin protection

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.



Environmental exposure controls

Do not allow to enter drains or water courses.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**(a) Physical state**

Liquid

**(b) Colour**

Diverse.

**(c) Odour**

Fruit-like odour.

**(d) Melting point/freezing point**

Not applicable due to nature of the product.

**(e) Boiling point or initial boiling point and boiling range**

#N/A

**(f) Flammability**

Vapours are ignitable. See Flash point (h).

**(g) Lower and upper explosion limit**

The product itself is not explosive, but the formation of an explosive mixture of vapour or dust with air is possible.

|  |                 |
|--|-----------------|
| 2-Methoxy-1-Methylethyl Acetate.   | 1.3-13.1%       |
| Xylene.  | 1.0-7.0%        |
| Ethyl Methyl Ketone.   | 1.8-11.5%       |
| Ethylbenzene.  | 1.2-8.0%        |
| Reaction Mass Of A-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl)Propionyl-Ω-Hydroxypoly (Oxyethylene) And A-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl)Propionyl-Ω-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl) | Not applicable. |
| Bis (1,2,2',6,6'-Pentamethyl-4-Piperidyl)Sebacate.   | Not applicable. |



Product code: 573PZ - Version 2.2 - Revision Date: 21-12-2015

**(h) Flash point**

43°C - Method: ISO13736:2021

**(i) Auto-ignition temperature**

Not applicable due to nature of the product.

#N/A

**(j) Decomposition temperature**

Not applicable due to nature of the product.

**(k) pH**

Not applicable due to nature of the product. Mixture is non-soluble (in water).

**(l) Kinematic viscosity**

>20,5 mm<sup>2</sup>/s @40°C - Method: ISO3219

Non-Newtonian liquid - thixotropic behaviour.

**(m) Solubility**

Not Soluble (in water).

**(n) Partition coefficient n-octanol/water (log value)**

Not applicable due to nature of the product.

**(o) Vapour pressure**

|  |           |
|--|-----------|
| 2-Methoxy-1-Methylethyl Acetate.   | 3.55 mbar |
| Xylene.  | 8.0 mbar  |
| Ethyl Methyl Ketone.   | 105 mbar  |
| Ethylbenzene.  | 9.3 mbar  |
| Reaction Mass Of A-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl)Propionyl-Ω-Hydroxypoly (Oxyethylene) And A-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl)Propionyl-Ω-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl) | 0,00009Pa |
| Bis (1,2,2',6,6'-Pentamethyl-4-Piperidyl)Sebacate.   | 1E-4 Pa   |

**(p) Density and/or relative density**

Relative density 1,39 @ 20°C - Method: ASTM D1475-98

**(q) Relative vapour density**

1-2 @ 20°C - Method: Calculated.

**(r) Particle characteristics**

Not applicable due to nature of the product.

**9.2. Other information**

Information with regard to physical hazard classes

No relevant information.

Other safety characteristics

No relevant information.

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No specific test data related to reactivity available for this product or its ingredients.

**10.2. Chemical stability**

Stable under recommended storage and handling conditions (see Section 7).

**10.3. Possibility of hazardous reactions**

In combination with oxidizing agents, strongly alkaline and strongly acid materials, exothermic reactions and/or explosive reactions may occur or toxic vapours may arise.



Product code: 573PZ - Version 2.2 - Revision Date: 21-12-2015

#### 10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

#### 10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials.

#### 10.6. Hazardous decomposition products

Carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

### SECTION 11: Toxicological information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

#### Substance name

2-Methoxy-1-Methylethyl Acetate. - LD50 Oral - 8532 mg/kg, Rat - LD50 Dermal - >5000 mg/kg, Rat - LC50 Inhalation - >20 mg/lRat

Xylene. - LD50 Oral - >2000 mg/kg, Rat - LD50 Dermal - >2000 mg/kg, Rat - LC50 Inhalation - 29 mg/lRat,4h

Ethyl Methyl Ketone. - LD50 Oral - >2000 mg/kg, Rat - LD50 Dermal - >2000 mg/kg, Rabbit - LC50 Inhalation - >20 mg/lRat,4h

Ethylbenzene. - LD50 Oral - >3000 mg/kg, Rat - LD50 Dermal - >5000 mg/kg, Rabbit - LC50 Inhalation - 17,8 mg/lRat,4h

Reaction Mass Of A-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl)Propionyl-Ω-Hydroxypoly (Oxyethylene) And A-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl)Propionyl-Ω-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl) Propionyloxypoly(Oxyethylene). - LD50 Oral - >5000 mg/kg, Rat - LD50 Dermal - >2000 mg/kg, Rat - LC50 Inhalation - 5,8 mg/lRat,14d

Bis (1,2,2',6,6'-Pentamethyl-4-Piperidyl)Sebacate. - LD50 Oral - 3200 mg/kg, Rat - LD50 Dermal - >2000 mg/kg, Rat - LC50 Inhalation - Not available.

#### Acute toxicity:

ATEmix (oral)

ATEmix (Dermal)

ATEmix (Inhalation)

#### Conclusion/Summary on mixture

: No specific data.

: No specific data.

: No specific data.

#### Skin corrosion/irritation:

Conclusion/Summary on mixture: Causes skin irritation.

Method: Additivity approach, No testdata available.

#### Serious eye damage/irritation:

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met.

Justification: Additivity approach, No testdata available.

#### Respiratory or skin sensitisation:

Conclusion/Summary on mixture

Respiratory sensitization Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.



Product code: 573PZ - Version 2.2 - Revision Date: 21-12-2015

Skin sensitization Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

**Germ cell mutagenicity:**

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

**Carcinogenicity:**

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

**Reproductive toxicity:**

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

**STOT - single exposure:**

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

**STOT - repeated exposure:**

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

**Aspiration hazard:**

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met.  
Justification: Additivity approach / Kinematic viscosity: >20,5 mm<sup>2</sup>/s @40°C - Measured

**Information on likely routes of exposure**

Inhalation: No known significant effects or critical hazards.

Ingestion: No specific data.

Skin exposure: Causes skin irritation.

Eye exposure: No specific data.

**Symptoms related to the physical, chemical and toxicological characteristics**

Inhalation: No specific data.

Ingestion: No specific data.

Skin exposure: Adverse symptoms may include the following: irritation, redness.

Eye exposure: Adverse symptoms may include the following: irritation, watering, redness.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Short term exposure:**

Potential immediate effects: No specific data.

Potential delayed effects: No specific data.

**Long term exposure:**

Potential immediate effects: No specific data.

Potential delayed effects: No specific data.

**Potential chronic health effects:**

Conclusion/Summary on mixture

General: No known significant effects or critical hazards.

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: No known significant effects or critical hazards.

Developmental effects: No known significant effects or critical hazards.

Fertility effects: No known significant effects or critical hazards.

Other information: No relevant information.



Product code: 573PZ - Version 2.2 - Revision Date: 21-12-2015

## 11.2 Information on other hazards

Endocrine disrupting properties

No relevant information.

Other information

No relevant information.

## SECTION 12: Ecological information

There are no data available on the mixture itself. Do not allow to enter drains or water courses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified for eco-toxicological hazards.

### 12.1. Toxicity

#### Substance name - Species - Exposure - Results

2-Methoxy-1-Methylethyl Acetate. Acute (short-term) toxicity: Fish: LC50/96h 130 mg/l (Pimephales promelas), Crustacea: EC50/48h 408-500 mg/l (Daphnia magna), Algae/aquatic plants: EC50/72h 1000 mg/l (Selenastrum capricornutum), Other organisms: Not available. Chronic (long-term) toxicity: Fish: NOEC 47.5 mg/L (Oryzias latipes), Crustacea: NOEC ≥ 100 mg/l, Algae/aquatic plants: NOEC ≥ 1,000 mg/l, Other organisms: Not available.

Xylene. Acute (short-term) toxicity: Fish: LC50/96h - 2.6 mg/l, Crustacea: EC50/48h 1-10 mg/l (Daphnia magna), Algae/aquatic plants: EC50/72h 2.2 mg/L (Pseudokirchneriella subcapitata), Other organisms: Not available. Chronic (long-term) toxicity: Fish: NOEC >1.3 mg/L (Salmo gairdneri), Crustacea: NOEC 0.96mg/L, Algae/aquatic plants: NOEC 0.44mg/L, Other organisms: Not available.

Ethyl Methyl Ketone. Acute (short-term) toxicity: Fish: LC50/96h 2993 mg/l (Pimephales promelas), Crustacea: EC50/48h 308 mg/l (Daphnia magna), Algae/aquatic plants: EC50/96h 2029 mg/L (Pseudokirchneriella subcapitata), Other organisms: Not available. Chronic (long-term) toxicity: Fish: Not available., Crustacea: Not available., Algae/aquatic plants: NOEC 1240 mg/L, Other organisms: Not available.

Ethylbenzene. Acute (short-term) toxicity: Fish: LC50/96h 4.2 mg/l (Oncorhynchus mykiss) / LC50/96 5.1 mg/L (Menidia menidia), Crustacea: EC50/48h 1.8 mg/l (Daphnia magna) / EC50/48h 2.6 mg/L (mysid shrimp), Algae/aquatic plants: EC50/96h 3.6 mg/L (Pseudokirchneriella subcapitata) / EC50/96h 7.7 mg/L (Skeletonema costatum), Other organisms: Not available. Chronic (long-term) toxicity: Fish: Not available., Crustacea: Not available., Algae/aquatic plants: NOEC 3,4 / NOEC 4,5 mg/L. Other organisms: Not available.

Reaction Mass Of A-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl)Propionyl-Ω-Hydroxypoly (Oxyethylene) And A-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl)Propionyl-Ω-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl) Propionylxypoly(Oxyethylene). Acute (short-term) toxicity: Fish: LC50/96h 2,8mg/l (Oncorhynchus mykiss), Crustacea: EC50/48h 4,0 mg/l (Daphnia magna), Algae/aquatic plants: EC50/72h >9 mg/l (Pseudokirchneriella subcapitata), Other organisms: LC50/14d >1000 mg/kg soil, www.Eisenia.foetida Chronic (long-term) toxicity: Fish: LC50/4d 3.8 mg/L (Lenomis macrochirus), Crustacea: NOEC 0.23 mg/L, Bis (1,2,2',6,6'-Pentamethyl-4-Piperidyl)Sebacate. Acute (short-term) toxicity: Fish: LC50/96h 0.90 mg/L (Danio rerio), Crustacea: Not available., Algae/aquatic plants: EC50/72h 1,68 mg/L (Desmodesmus subspicatus), Other organisms: Not available. Chronic (long-term) toxicity: Fish: Not available., Crustacea: Not available., Algae/aquatic plants: Not available., Other organisms: Not available.

### 12.2. Persistence and degradability

#### Substance name

2-Methoxy-1-Methylethyl Acetate. - Readily biodegradable.

Xylene. - Readily biodegradable.

Ethyl Methyl Ketone. - Readily biodegradable.

Ethylbenzene. - Readily biodegradable.

Reaction Mass Of A-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl)Propionyl-Ω-Hydroxypoly (Oxyethylene) And A-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl)Propionyl-Ω-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl) Propionylxypoly(Oxyethylene). - Not biodegradable.



Product code: 573PZ - Version 2.2 - Revision Date: 21-12-2015

**12.2. Persistence and degradability**

**Substance name**

Bis (1,2,2',6,6'-Pentamethyl-4-Piperidyl)Sebacate. - Not available.

**12.3. Bioaccumulative potential**

**Substance name**

| Substance name  | log Kow | BCF            |
|---|---------|----------------|
| 2-Methoxy-1-Methylethyl Acetate.  | 1,2     | Not available. |
| Xylene.   | 3,1     | 25,9           |
| Ethyl Methyl Ketone.  | 0,3     | -              |
| Ethylbenzene.   | 3,6     | 110 L/kg ww    |
| Reaction Mass Of A-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl)Propionyl-Ω-Hydroxypoly (Oxyethylene) And A-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl)Propionyl-Ω-3-(3-(2H-Benzotriazol-2-Yl)-5-Tert-Butyl-4-Hydroxyphenyl)Prorinonoloxypoly(Oxyethylene). | <-1,3   | Not available. |
| Bis (1,2,2',6,6'-Pentamethyl-4-Piperidyl)Sebacate.  | 2,37    | Not available. |

**12.4. Mobility in soil**

Soil/water partition coefficient (KOC) : Not available.  
 Mobility : No relevant information.

**12.5. Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6. Endocrine disrupting properties**

No relevant information.

**12.7. Other adverse effects**

Not available.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**




Product / Packaging disposal: Dispose of containers contaminated by the product in accordance with local or national legal provisions. The European Waste Catalogue (2014/955/EC) classification of this product. Waste codes / waste designations according to LoW: 08 01 11\* Waste paint and varnish containing organic solvents or other hazardous substances. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information contact your local waste authority. Waste should not be disposed of by release to sewers. Using information provided in this safety data sheet, advice should be obtained from the local waste authority on the classification of empty containers.  
 Containers which are not properly cleaned may contain (highly) flammable or explosive vapours.  
 Special precautions: Use appropriate protective equipment for the removal and / or disposal of this product.

**SECTION 14: Transport information**

|                                     | ADR / RID / ADN | IMDG-Code | IATA    |
|-------------------------------------|-----------------|-----------|---------|
| <b>14.1. UN number or ID number</b> | UN 1263         | UN 1263   | UN 1263 |



Product code: 573PZ - Version 2.2 - Revision Date: 21-12-2015

|   | ADR / RID / ADN   | IMDG-Code  | IATA  |
|---|---|--|---|
| <b>14.2. UN proper shipping name</b>    | PAINT   | PAINT  | PAINT   |
| <b>14.3. Transport hazard class(es)</b> | 3   | 3  | 3   |
| Label(s)                                |  |  |  |
| <b>14.4. Packing group</b>              | III   | III  | III   |
| <b>14.5. Environmental hazards</b>      | No  | No<br>Marine Pollutant: No   | No  |
| Additional information                  | Hazard Identification Number No.:<br>30   | Emergency Schedule Number (EmS): F-E, S-E  |   |

**14.6. Special precautions for user**

Transport within the user's premises: Always transport in closed containers that are upright and secure.  
 Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7. Maritime transport in bulk according to IMO instruments**

Not applicable.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

The information in this Safety Data Sheet is required pursuant to Annex II to regulation (EC) No 1907/2006 and its amendments.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

Seveso category (DIRECTIVE 2012/18/EU): P5c This product may add to the calculation for determining whether a site is within scope of the Seveso Directive on major accident hazards.



Product code: 573PZ - Version 2.2 - Revision Date: 21-12-2015

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

**SECTION 16: Other information****Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:**

|      |                     |
|------|---------------------|
| H226 | Measured            |
| H315 | Additivity approach |

**Abbreviations and acronyms:**

ADN : European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE : Acute Toxicity Estimate  
BCF : Bioconcentration factor  
CLP : Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008  
DNEL : Derived No Effect Level  
IATA : International Air Transport Association  
IMDG-Code : International Maritime Dangerous Goods  
Kow : octanol-water partition coefficient  
LC50 : Lethal Concentration to 50 % of a test population  
LD50 : Lethal Dose to 50% of a test population (Median Lethal Dose)  
PBT : Persistent, Bioaccumulative and Toxic substance  
PNEC : Predicted No Effect Concentration(s)  
RID : Regulations concerning the International Carriage of Dangerous Goods by Rail  
STOT : Specific Target Organ Toxicity  
vPvB : Very Persistent and Very Bioaccumulative



Product code: 573PZ - Version 2.2 - Revision Date: 21-12-2015

**Full text of Hazard Statements appearing in Section 3.2.:**

|        |  |
|--------|--|
| EUH066 | Repeated exposure may cause skin dryness or cracking.              |
| H225   | Highly flammable liquid and vapour.                                |
| H226   | Flammable liquid and vapour.                                       |
| H304   | May be fatal if swallowed and enters airways.                      |
| H312   | Harmful in contact with skin.                                      |
| H315   | Causes skin irritation.  |
| H317   | May cause an allergic skin reaction.                               |
| H319   | Causes serious eye irritation.                                     |
| H332   | Harmful if inhaled.  |
| H336   | May cause drowsiness or dizziness.                                 |
| H373   | May cause damage to organs through prolonged or repeated exposure. |
| H400   | Very toxic to aquatic life.  |
| H410   | Very toxic to aquatic life with long lasting effects.              |
| H411   | Toxic to aquatic life with long lasting effects.                   |

Amendments: 21-12-2015, §3 &amp; 16

The information of this SDS is based on the present state of our knowledge and on current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.